

# MASTER B.C.

Neodoljivi osjećaj sigurnosti

## CJENOVNIK OPREME ZA VIDEO NADZOR



**BOSCH**

**Imou**

# Sadržaj

Dahua HDCVI kamere, 2MP.....	3
Dahua HDCVI kamere, 5MP.....	8
Dahua HDCVI kamere, 8MP/4K.....	11
Dahua HDCVI PTZ kamere.....	13
Dahua HDCVI digitalni video snimači.....	14
Dahua HDCVI snimači 4K-N/5MP serije (4KL).....	16
Dahua HDCVI mobilni snimači.....	18
Dahua IP kamere, 2MP i 3MP.....	19
Dahua IP kamere, 4MP.....	23
Dahua IP kamere, 5MP.....	26
Dahua IP kamere, 6MP.....	30
Dahua IP kamere, 8MP/4K.....	31
Dahua IP kamere, specijalne.....	34
Dahua Wi-Fi kamere.....	36
Dahua IP PTZ kamere.....	38
Dahua IP mrežni video snimači Lite Serija 4.....	43
Dahua IP mrežni video snimači.....	47
Dahua Ethernet i PoE svičevi, SFP moduli.....	50
IMOU WiFi kamere, 2MP.....	56
IMOU WiFi kamere, 3MP.....	58
IMOU WiFi kamere, 4MP.....	59
IMOU WiFi kamere, 5MP.....	61
IMOU WiFi kamere, 8MP.....	63
IMOU WiFi kamere, 10MP.....	64
IMOU SET.....	65
Sony IP kamere.....	66
Western Security AHD kamere.....	67
Western Security AHD digitalni video snimači.....	68
Monitoring oprema.....	69
Monitori za video nadzor.....	70
Dodatna oprema.....	72
Hard diskovi.....	77
SD kartice.....	80
Dahua dozne i nosači.....	82
Napajanja.....	88
HDMI kablovi, spliteri, ekstenderi.....	93
Alati i testeri.....	94
Konektori.....	95
Alarmni kablovi - licnasti.....	98
Koaksijalni kablovi.....	99
Optike.....	101
Outlet.....	103



## HAC-B1A21-0360B bulett kamera

VK-939

2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.04Lux/F2.0, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 20 metara. 12v napajanje. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Plastika.

Cijena i dobavlјivost na upit



## HAC-TIA21-0280B Dome kamera

VK-851

2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.04Lux/F2.0, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. DWDR. Domet IC dioda 20 metara. 12v napajanje. Odgovarajuća dozna je PFA135. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Plastika.

Cijena i dobavlјivost na upit



## HAC-B2A21-0360B bulett kamera

VK-858

2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.04Lux/F1.85, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 20 metara. 12v napajanje. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HFW2249T-I8-A-NI-0360B kamera Rasprodaja

VK-895

2MP Full-color Starlight HDCVI kamera u bullet kućištu

4 u 1 TVI/AHD/CVI/CVBS režim. Min. osvjetljenje: 0.001Lux/F1.0, potreban vanjski izvor osvjetljenja, Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. 120dB WDR. Integriran mikrofoni. 12V napajanje, max 2.4 W, Odgovarajuća baza PFA130-E, PFA135, za stub PFA135/PFA130-E + PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HFW1200CM-IL-A-0360B-S6 bulett kamera

VK-1098

2MP HDCVI Smart Dual Light kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.01Lux/F2.0. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Integriran mikrofoni. Domet IC/LED dioda 20 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HDW1200T-IL-A-0280B-S6 kamera

VK-906-1

2MP Smart Dual Light eyeball kamera

4 u 1 TVI/AHD/CVI/CVBS režim. 0.01Lux/F2.0, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67, radna temperatura -40 °C do +60 °C. DWDR. Integriran mikrofoni; Domet IC dioda 30metara, domet led- 40m. Odgovarajuća baza PFA139 ili PFA130-E, za zid PFB204W, nosač za stub PFB204W + PFA152-E Materijal: Metal

Cijena i dobavlјivost na upit





## HAC-HDW1200TMQ-A-0280B DOM kamera

2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.02Lux/F1.9, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 60 metara. Integrisan mikroskop. 12v napajanje. Odgovarajuća dozna je PFA137, PFA130-E. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal i Plastika.

VK-901

Cijena i dobavlјivost na upit



## HAC-HDBW1200EA-0280B-S6 kamera

2MP fiksna antivandal kamera u dom kućištu

2 MP CMOS senzor. Color: 0.01lux / F2.0 (Color). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. DWDR. Domet IC dioda 40 metara. Napajanje 12VDC, 2.8W max. Nivo zaštite IP67, IK10, radna temperatura -40 °C do +60 °C. Odgovarajuća baza PFA136, nosač za stub PFB203W + PFA152-E, zidni nosač PFB305W. Materijal: Metal.

VK-1109

Cijena i dobavlјivost na upit



## HAC-HUM3200A-0280P-S5 kamera

2MP HDCVI kamera u cube kućištu.

0.01Lux/F2.0. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. DWDR. Domet IC dioda 10 metara. 12v napajanje. Materijal: Plastika.

VK-1079

Cijena i dobavlјivost na upit



## HAC-HDW1231TLMQ-A-0280B kamera

2MP Starlight HDCVI IR brzo-instalirajuća kamera u eyeball kućištu

4 u 1 TVI/AHD/CVI/CVBS režim. Min. osvjetljenje 0.002Lux/F1.6, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. WDR 130dB. Domet IC dioda 30 metara. Odgovarajuća baza PFA136, PFA130-E, PFA13G, nosač za stub PFB203W + PFA152-E, zidni nosač PFB203W. Materijal: Metal i plastika.

VK-928

Cijena i dobavlјivost na upit



## HAC-HFW1231TLM-I6-A-0360B bulet kamera

2MP Starlight IR HDCVI kamera u bullet kućištu

0.002Lux/F1.6, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67, radna temperatura -40 °C do +60 °C. True WDR 130dB, Super Adapt. Domet IC dioda 60 metara. Integrisan mikroskop. 12V napajanje 5.1W max. Odgovarajuća baza PFA134/PFA130-E, za stub PFA134/PFA130-E + PFA152-E. Materijal: Metal i plastika.

VK-963

Cijena i dobavlјivost na upit



## HAC-HFW1239TLM-A-LED-0360B-S2 kamera

2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim, Full-color, Starlight.

0.001Lux/F1.6, 30IRE, 0Lux white Light on. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 40 metara. Integrisan mikroskop. 12v napajanje. Odgovarajuća dozna je PFA134, PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal i Plastika.

VK-914

Cijena i dobavlјivost na upit



## HAC-HDW1239T-A-LED-0280B-S2 kamera

VK-913

2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim, Full-color, Starlight.

0.001Lux/F1.6, 30IRE, 0Lux white Light on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 40 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA139. Nosač za banderu je PFA152-E. Zidni nosač je PFB204W. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HFW1231TM-I8-A-0360B bulit kamera

VK-963-1

2MP Starlight HDCVI IR kamera u bullet kućištu

HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/ CVI/CVBS režim. Min. osvjetljenje: 0.002Lux/F1.6. 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. True WDR 130dB. Domet IC dioda 80 metara. Integriran mikrofoni. 12V napajanje 5.1W max. Odgovarajuća baza PFA135/PFA130-E, za stub PFA135/PFA130-E + PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-T3A21-Z-2712 dom kamera

VK-825-1

2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim

0.04Lux/F1.7, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7- 12mm. Nivo zaštite IP67. DWDR. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal i plastika.

Cijena i dobavlјivost na upit



## HAC-B3A21-Z-2712 kamera

VK-872

2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.04Lux/F1.7, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA13G. Nosač za banderu je PFA152-E. Materijal: Metal i plastika.

Cijena i dobavlјivost na upit



## HAC-HDBW1200R-Z-2712-S4 kamera

VK-755

2MP HDCVI kamera u dome kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.02Lux/F1.8, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA137, PFA123. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal i Plastika.

Cijena i dobavlјivost na upit



## HAC-HFW1200R-Z-A-2712-S6 kamera

VK-749-1

2MP HDCVI IR kamera u bullet kućištu

1/2.7 CMOS senzor. Min. osvjetljenje: 0.01 lux@F1.6 (Color, 30 IRE). Maksimalna rezolucija 1920x1080. Motorizovani varifokal 2.7-12mm. IR- 80m Nivo zaštite IP67. DWDR. 12V napajanje, max 9.4W, Odgovarajuća baza PFA130-E, za stub PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HDW1200T-Z-A (S5) kamera

VK-748-1

2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.02Lux/F1.7, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 60 metara. Integrisan mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HUM3201B-P-02080B-S2 pinhole kamera

VK-942

2MP HDCVI kamera u pinhole kućištu.

Color: 0.004LuxLux/F2.4Black & White: 0.0004LuxLux/F2.4. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. 120dB WDR. 1x audio in. 12v napajanje. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HDBW3231EP-ZH kamera Rasprodaja

VK-583

2MP HDCVI kamera u dome kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim.

0.005Lux/F1.4, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 50 metara. 12v napajanje. Odgovarajuća dozna je PFA138. Nosač za banderu je PFA150. Zidni nosač je PFB302S. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HFW1231R-Z-A-2712 kamera

VK-927

2MP HDCVI kamera u bullet kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim.

0.002Lux/F1.5, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. 130dB WDR. Domet IC dioda 80 metara. Integrisan mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA13G. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HDBW2241F-M-A kamera

VK-958

2MP anti-vandal dome HDCVI IR kamera

1/2.8" CMOS sa progresivnim skeniranjem. Efektivni broj piksela 1920(H) x 1080(V). Rezolucija 1080P@25 fps ili 960H@25 fps. Osetljivost: 0.004Lux/F1.6. Smart IC LED diode dometa 20m. 120dB WDR. Nivo zaštite: IP67, IK10. Audio: ima integrisan mikrofoni. Materijal: aluminijum.

Cijena i dobavlјivost na upit



## HAC-HFW1239TU-Z-A-LED-27135-S2

VK-929

2MP Full-color HDCVI u bullet kućištu

StarLight tehnologija 4 u 1 TVI/AHD/CVI/CVBS režim. Min. osvjetljenje: 0.001 Lux/F1.2, 30IRE, 0 Lux LED on. Maksimalna rezolucija 1920x1080. Motorizovani objektivi 2.7 mm-13.5 mm. Auto focus. Nivo zaštite IP67. WDR 130dB. Domet IC dioda 60 metara. Integrisan mikrofoni. 12V napajanje 10.2W max. odgovarajuća baza PFA135, Waterproof PFA130-E, nosač za stub PFA130-E + PFA152-E. Materijal: metal.

Cijena i dobavlјivost na upit



**dahua**  
TECHNOLOGY



## HAC-HFW1200CL-IL-A-0280B-S6

2MP HDCVI Smart Dual Light kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.01Lux/F2.0. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Integrisan mikrofoni. Domet IC/LED dioda 20 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: plastika.

VK-908-1

Cijena i dobavljaljivost na upit

**dahua**  
TECHNOLOGY



## HAC-HFW1239TLM-A-LED-0280B-S3 kamera

2MP Full-color, HDCVI kamera u bullet kućištu

0.001 lux@F1.0, 30IRE, 0Lux LED. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. 130dB WDR. Domet LED dioda 40 metara. Integrisan mikrofoni. Nivo zaštite IP67, 12V napajanje, potrošnja Max 7.79W. Odgovarajuća dozna je PFA134, PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal i Plastika.

VK-914-1

Cijena i dobavljaljivost na upit



## HAC-HDW1500TRQ-0280B-S2 dom kamera

VK-871

5MP HDCVI kamera u eyeball kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim.

0.005 Lux/F1.6, 30IRE, 0 Lux IR on. Maksimalna rezolucija 2880x1620. Fiksna optika 2.8 mm. Nivo zaštite IP50. DWDR. Domet IC dioda 25 metara. 12v napajanje. Odgovarajuća dozna je PFA13G. Nosač za banderu je PFA152-E. Zidni nosač je PFB205W. Materijal: Plastika.

Cijena i dobavlјivost na upit



## HAC-HFW1500CL-IL-A-0360B-S2 kamera

VK-917-1

5MP Smart Dual Light bulit kamera

4 u 1 TVI/AHD/CVI/CVBS režim. 0.05Lux/F1.6, 30IRE, 0Lux LED on. Maksimalna rezolucija 2880x1620. Fiksna optika 3.6mm. Nivo zaštite IP67, radna temperatura -40 °C do +60 °C. DWDR. Integrisan mikrofون; Domet IC dioda 20metara, domet led- 20m. Odgovarajuća baza PFA130-E, PFA134, nosač za stub PFA152-E. Materijal: plastika

Cijena i dobavlјivost na upit



## HAC-HFW1500T-A-0280B kamera

VK-864

5MP HDCVI IR vodootporna kamera u bullet kućištu

1/2.7 5 MP CMOS camera. Min. osvjetljenje: 0.02Lux @ F1.85, 30IRE (0Lux IR Led on). Fiksni objektiv: 2.8mm, ugrađen MIKROFON, OSD meni, izbor HD i SD izlaza. IR LEDs: 30m, Smart IR. DWDR, Day&Night (ICR), AWB, AGC, BLC, HLC, 2D-DNR, IP67 metalno kućište, DC12V, 3.7W. Odgovarajuća dozna PFA134, nosač za stub PFA134 + 152-E.

Cijena i dobavlјivost na upit



## HAC-HFW1500TL-A-0360-S2 kamera

VK-790-1

5MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.01 Lux/F1.6, 30IRE, 0 Lux IR on. Maksimalna rezolucija 2880x1620. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 80 metara. Integrisan mikrofون. 12v napajanje. Odgovarajuća dozna je PFA130-E ili PFA134. Nosač za banderu je PFA152-E. Materijal: Metal i Plastika.

Cijena i dobavlјivost na upit



## HAC-HDBW1500E-0280B-S2 kamera

VK-899

5MP HDCVI kamera u dome kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.01 Lux/F1.6, 30IRE, 0 Lux IR on. Maksimalna rezolucija 2880x1620. Fiksna optika 2.8 mm. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal i Plastika.

Cijena i dobavlјivost na upit



## HAC-HDBW2501E-0280B kamera

VK-751-1

5MP Starlight HDCVI IR antivandal kamera u Dome kućištu

Rezolucija ( 2592 x 1944). Osjetljivost: 0.005Lux @ F1.6 30IRE (0Lux IR Led on). Žižna daljina: 3.6mm / 2.8mm. Smart IR LED: 30m. WDR (True 120dB). Redukcija šuma: 2D/3DNR. Audio interfejs: 1 ch in. Napajanje: DC12V. Potrošnja: max 5.3W (IR ON). Zaštita: IP67, IK10. Odgovarajuća dozna PFA136, nosač za stub PFB203W + 152-E, zidni nosač PFB203W. Materijal: metal i plastika.

Cijena i dobavlјivost na upit







## HAC-HFW1509TLM-A-LED-0360B S2 full color kamera

VK-827

5MP Full-color HDCVI bulet kamera

0.001Lux/F1.0, 0Lux IR on. Maksimalna rezolucija 2880x1620. Fiksna optika 3.6mm. Nivo zaštite IP67. 120dB WDR. Domet LED dioda 40 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: Metal i Plastika.

Cijena i dobavlјivost  
na upit




## HAC-HDW1509T-A-LED-0280B-S2 dom full color kamera

VK-829-1

5MP HDCVI kamera u eyeball kućištu sa Full-color tehnologijom, 4 u 1 TVI/AHD/CVI/CVBS režim.

0.001Lux/F1.0, 30IRE, 0 Lux warm light on. Maksimalna rezolucija 2880x1620. Fiksna optika 2.8 mm. Nivo zaštite IP67. 120dB WDR. Domet LED dioda 40 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA139. Nosač za banderu je PFA152-E. Zidni nosač je PFB204W. Materijal: Metal.

Cijena i dobavlјivost  
na upit



## HAC-HDW2501TMQ-A-0280B-S2 DOM 5MP IR starlight kamera

VK-894

5MP Starlight HDCVI Quick-to-install IR kamera u eyeball kućištu

Rezolucija: 5 MP . Starlight: Da . Tip kućišta: Eyeball .Broj slika u sekundi: PAL: 5M@25 fps;4M@25 fps;1080P@25 fps.Optika:2.8 mm.IR domet: 60 m.WDR:120 dB.Video izlaz: BNC port CVI/TVI/AHD/CVBS. Audio: Ugrađen mikrofoni.Napajanje: Max 5.9W (12V DC, IR on).Zaštita: IP67. Dozna: PFA130-E/PFA137.Nosač za stub:PFA152-E. Nosač za zid: PFB203W.Materijal: metal i plastika.

Cijena i dobavlјivost  
na upit



## HAC-HFW1509TM-A-LED-0360B-S2 bulet full color kamera

VK-964

5MP Full-color HDCVI bulet kamera

1/2.7 CMOS sa progresivnim skeniranjem;0.001Lux/F1.0, 0Lux IR on. Maksimalna rezolucija 2880x1620, fiksna optika 3.6mm, nivo zaštite IP67, radna temperatura -40 °C do +60 °C. 120dB WDR. Domet LED dioda 40 metara. Integriran mikrofoni. 12V napajanje 6.4Wmax. Odgovarajuća baza PFA130-E, PFA135, za stub PFA135/PFA130-E + PFA152-E. Materijal: Metal

Cijena i dobavlјivost  
na upit



## HAC-HDW1500T-Z-A 2712 kamera

VK-767

5MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.005Lux/F1.6, 30IRE, 0Lux IR on. Maksimalna rezolucija 2880x1620. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 60 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost  
na upit



## HAC-HFW1500R-Z-IRE6-A-2712-S2 Bullet kamera 5MP 2.7-12mm

VK-739

5MP Starlight HDCVI IR kamera u bullet kućištu

4 u 1TVI/AHD/CVI/CVBS režim. Min. osvjetljenje:0.005Lux/F1.6, 0Lux IR on. Maksimalna rezolucija 2880x1620. Motorizovana promjenljiva optika 2,7-12mm. Nivo zaštite IP67.Domet IC dioda 60metara. DWDR, integriran mikrofoni. 12VDC napajanje 12Wmax. Odgovarajuća baza PFA135/ PFA13G/ PFA122/ PFA130-E, nosač za stub PFA135/PFA122/PFA130-E + PFA152-E. Materijal: Metal.

Cijena i dobavlјivost  
na upit





## HAC-ME1509TH-A-PV-0360B-S2 kamera Rasprodaja

5MP Active Deterrence HDCVI kamera u bullet kućištu

5MP CMOS senzor; Osvjetljenje 0.001Lux/F1.0, 0Lux IR on. Maksimalna rezolucija 2880x1620, fiksna optika 3.6mm, nivo zaštite IP67. 120dB WDR. IR LED 40 metara. Integriran mikrofoni. 12V napajanje 10.5W max. Odgovarajuća baza PFA130-E, za stub PFA152-E. Materijal: Metal i plastika.

VK-907-1

Cijena i dobavljaljivost  
na upit



## HAC-HFW2501TU-Z-A-27135-S2 kamera

5MP HDCVI kamera u bullet kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/ CVBS režim.

0.001 Lux/F1.6; 30IRE; 0 Lux IR on. Maksimalna rezolucija 2880x1620. Varifokalna optika 2.7 - 13.5 mm. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 80 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA135. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-956

Cijena i dobavljaljivost  
na upit



## HAC-HFW1500TLM-IL-A-0280B-S2

5MP HDCVI Smart Dual Light kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/ CVBS režim.

0.005Lux/F1.6. Maksimalna rezolucija 2880x1620. Fiksna optika 2.8mm. DWDR. Integriran mikrofoni. Domet IC/LED dioda 40 metara. 12v napajanje. Nivo zaštite IP67 Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: metal + plastika.

VK-864-1

Cijena i dobavljaljivost  
na upit



## HAC-HFW1500TH-I8-0360B-S2

5MP Starlight HDCVI IR kamera u bullet kućištu

4 u 1 TVI/AHD/ CVI/ CVBS režim. Min. osvjetljenje: 0.01 Lux/F1.6. 30IRE, 0Lux IR on. Maksimalna rezolucija 2880x1620. Fiksna optika 3.6mm. Nivo zaštite IP67. Domet IC dioda 80 metara. Integriran mikrofoni. 12V napajanje 5.2W max. Odgovarajuća baza PFA135/PFA130-E, za stub PFA152-E. Materijal: Metal i plastika.

VK-1146

Cijena i dobavljaljivost  
na upit



## HAC-HDW1500T-IL-A-0280B-S2 kamera

□  
5MP HDCVI Smart Dual Light kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/ CVBS režim.

0.05Lux/F1.6. Maksimalna rezolucija 2880x1620. Fiksna optika 2.8mm. DWDR. Integriran mikrofoni. Domet IC/LED dioda 40 metara. 12v napajanje. Nivo zaštite IP67, 12V Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: metal.

VK-910-1

Cijena i dobavljaljivost  
na upit



## HAC-HFW1509TLM-IL-A-0360B-S2 kamera

5MP Dual Light HDCVI bullet kamera

0.001Lux/F1.0, 0Lux IR on. Maksimalna rezolucija 2880x1620, fiksna optika 3.6mm. 120dB WDR. Domet IR/LED dioda 40 metara. Integriran mikrofoni. nivo zaštite IP67, 12V napajanje 5.7W max, radna temperatura -40 °C do +60 °C. Odgovarajuća baza PFA130-E, PFA135, za stub PFA135/PFA130-E + PFA152-E. Materijal: Metal

VK-827-1

Cijena i dobavljaljivost  
na upit



## HAC-HDW1800TL-A-0280B kamera

VK-854

4K Real-time HDCVI IR kamera u eyeball kućištu

Senzor 1/2.7 CMOS. Rezolucija:3840×2160, 4K@15 fps, 20 fps @5MP, 1080p. Min. osvjetljenost: 0.03Lux/F2.0, 0Lux IR on. Pametni IR: domet do 30m, ugrađen mikrofoni. Fiksni iris.OPTIKA 2.8mm. Video izlaz: 1 x BNC HD/CVBS preklopljeni. Dan/ Noć: Auto (ICR) / manual.Redukcija šuma: 2D.Napajanje: DC12V.Potrošnja: maks4.3W,IR on. Zaštita: IP67.Odgovarajuća baza PFA130, nosač za stub PFA130 + PFA152-E.

Cijena i dobavlјivost na upit



## HAC-HDW1800M-0280B dom kamera

VK-953

8MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.03Lux/F2.0, 30IRE, 0Lux IR on. Maksimalna rezolucija 3840x2160. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA13A-E. Nosač za banderu je PFA152-E. Zidno nosač je PFB204W. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HFW1800TL-A-0360B kamera

VK-863

4K Real-time HDCVI vodo-nepropusna bullet IR kamera

Senzor 1/2.7 CMOS. Rezolucija:3840×2160, 4K@15 fps, 20 fps @5MP, 1080p. Min. osvjetljenost: 0.03Lux/F2.0, 0Lux IR on. Pametni IR: domet do 80m. Optika 3.6 mm.Video izlaz: 1 x BNC HD/CVBS preklopljeni.Redukcija šuma: 2D. Napajanje: DC12V. Potrošnja: maks.6W,IR on. Zaštita: IP67.Kućište front metal tijelo plastika.Odgovarajuća dozna PFA134, PFA12A, nosač za stub PFA134 + 152-E.

Cijena i dobavlјivost na upit



## HAC-HFW1800T-A-0280B kamera

VK-843

8MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim.

0.03Lux/F2.0, 30IRE, 0Lux IR on. Maksimalna rezolucija 3840x2160. Fiksna optika 2.8 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integrisan mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## HAC-HDW2802T-A-0280B kamera Rasprodaja

VK-918

4K Starlight HDCVI IR kamera u eyeball kućištu

Rezolucija: 8 MP (4K).Starlight: Da .Tip kućišta: Eyeball. Broj slika u sekundi: 15fps@4K, 20fps@6MP, 25/30fps@4MP.Optika: 2.8 mm. IR domet: 50 m. WDR: 120 dB.Audio: Ugrađen mikrofoni, 1ch ulaz. Napajanje: Max 8W (12V DC, IR on). Zaštita: IP67. Dozna: PFA130-E. Nosač za stub:PFA152-E. Nosač za zid: PFB204W.Materijal:aluminium.

Cijena i dobavlјivost na upit



## HAC-HDW1801T-Z-A-27135 kamera

VK-905

4K HDCVI vodo-nepropusna IR kamera u eyeball kućištu

Senzor 1/2.7 CMOS;CVI/CVBS/AHD/TVI.Rezolucija:3840×2160. Min. osvjetljenost: 0.03Lux/F1.7, 0Lux IR on.Pametni IR: domet do 60m.Motorizovana optika-2.7-13.5mm. Video izlaz: 1x BNC.Dan/ Noć: Auto (ICR)/manual ugrađen mikrofoni.WDR 120dB.Redukcija šuma:2D/3D.Napajanje:DC12V.Potrošnja:maks. 7.8W. Zaštita:IP67. Odgovarajuća baza PFA130-E, nosač za stub PFB203W + PFA152-E, nosač na zid PFB203W.

Cijena i dobavlјivost na upit





## HAC-HDW2802T-Z-A-3711 kamera

VK-915

4K Starlight HDCVI IR kamera u eyeball kućištu

Rezolucija: 8 MP (4K).Starlight: Da. Tip kućišta: Eyeball. Broj slika u sekundi: 15fps@4K, 20fps@6MP, 25/30fps@4MP. Optika: Motorizovana 3.7-11mm.IR domet: 60 m. WDR: 120 dB. Video izlaz: BNC port CVI/CVBS. Audio: Ugrađen mikrofoni, 1ch ulaz. Napajanje: Max 9.5W (12V DC, IR on).Zaštita: IP67.Dozna: PFA130-E. Nosač za stub:PFA152-E. Nosač za zid: PFB203W.

Cijena i dobavlјivost  
na upit



## HAC-HFW2802TU-Z-A-27135-S2-DIP kamera

VK-1110

4K Starlight HDCVI vodo-nepropusna STARLIGHT IR kamera

Senzor 4K CMOS. Rezolucija:3840×2160, 4K@15 fps, 20fps@6MP, 25/30fps@4MP.Min. osvjetljenje: 0.001 lux@F1.5, 0Lux IR on. Pametni IR: domet do 80m. Fiksni iris.OPTIKA motorizovana-2.7-13.5mm. Video izlaz: 1 x BNC. Dan/ Noć: Auto (ICR) / manual UGRADJEN MIKROFON.WDR ( true120dB).Redukcija šuma: 2D/3D Napajanje: DC12V .Potrošnja: maks10.9W,IR on. Zaštita:IP67. Odgovarajuća baza PFA130-E, nosač za stub PFA130-E + PFA152-E, nosač za ugao PFA130-E + PFA151.

Cijena i dobavlјivost  
na upit



## HAC-HDBW1801E-0360 kamera Rasprodaja

VK-788

4K HDCVI vodo-nepropusna IR kamera

Senzor 1/2.7 CMOS. Rezolucija:3840×2160, 4K@15 fps, 20 fps @5MP, Min. osvjetljenje: 0.03Lux/F2.0, 0Lux IR on. IR: domet do 30m. Fiksni iris. OPTIKA 3.6mm. Video izlaz: 1 x BNC AHD/CVBS preklopljeni.Dan/ Noć: Auto (ICR) / manual. OSD meni. BLC/HLC/ WDR. WDR 120dB.Redukcija šuma: 2D/3D. Napajanje: DC12V. Potrošnja: maks4.8W,IR on. Zaštita:IP67,IK 10. Odgovarajuća baza PFA136, zidni nosač PFB203W, nosač za stub PFB203W + PFA152-E

Cijena i dobavlјivost  
na upit



**HAC-SD6CE230I-HC-S3 PTZ kamera**  
**Rasprodaja**

2MP Starlight HDCVI PTZ antivandal IR kamera

1/2.8 STARVIS CMOS senzor, prikaz 25/30fps@1080P, 25/30/50/60fps@720P. Optički zum: 30 x (4.5mm-135mm) +16 x digitalni. Osjetljivost: 0.005Lux@F1.6. WDR: 120 dB, Dan/ noć: Auto(ICR) / kolor/ w&b.IR domet: 200m.PTZ mod: auto scan, auto pan, 8 tour, 5 pattern. Privacy masking 24 oblasti. Audio: 1 in, alarm 2-ulaza/1-izlaz. IP67, IK10. Napajanje: 24VAC/3A 17W (25W IR i grijač uklj.).Video izlaz: 1 x HDCVI/ CVBS preklopljen. Dolazi sa PFB305W i adapterom 24VAC/3A, opciono PFA111 + PFB300C, PFB305W + PFA120, PFB305W + PFA151, PFB305W + PFA150. Materijal: Metal.

VK-653-1

Cijena i dobavlјivost na upit



**HAC-SD22204-GC-LB PTZ kamera**  
**Rasprodaja**

2MP HDCVI kamera u antivandal dom kućištu sa Starlight tehnologijom

1/2.8" CMOS sa progresivnim skeniranjem.Color: 0.05 Lux@F1.6, B/W: 0.005 Lux@F1.6 0 Lux@F1.6 (IR on).Maksimalna rezolucija 1920x1080. Motorizovana promjenljiva optika 2.7 - 11 mm. Optički zum 4x, digitalni zum 16x. Nivo zaštite IP66, IK10, 120dB WDR. 12VDC napajanje 6W, za napajanje potreban adapter 12V 1.5A ne dolazi uz kameru. Odgovarajuća baza PFA137, zidni nosač PFB203W, nosač za stub PFB203W+PFA152-E, opciono PFA106 + PFB220C. Materijal: Metal.

VK-584-1

Cijena i dobavlјivost na upit



**HAC-SD59225-HC-LA kamera Rasprodaja**

2MP HDCVI kamera u PTZ kućištu sa Starlight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux@F1.6 (IR on). Maksimalna rezolucija 1920x1080. Varifokalna optika 4.8 - 120 mm. Optički zum 25x. Nivo zaštite IP66. 120dB WDR. Domet IC dioda 150 metara. 1x audio in. 2x alarm in,1x alarm out. 12v napajanje. Dolazi sa nosačem za zid PFB300S|. Dozna PFA120. Ugaoni nosač PFA151. Nosač za banderu je PFA150.

VK-932

Cijena i dobavlјivost na upit



## XVR1B04-I snimač

VR-465

Penta-brid video snimač sa 4 analogna kanala plus 1 dodatni ip kanal rezolucije do 2MP.

Maksimalna rezolucija snimanja 1080N. Frame rate: 1080N (1~25/30fps). Bandwidth In 20Mbps, Bandwidth Out 20Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 6TB. SMD Plus.

Cijena i dobavlјivost na upit



## XVR1B08-I snimač

VR-466

Penta-brid video snimač sa 8 analogna kanala plus 2 dodatnih IP kanala rezolucije do 6MP.

Maksimalna rezolucija snimanja 2MP. Frame rate: Prvi kanal: 1080N (1fps~25/30fps) ostali kanali: 1080N (1fps~15fps). Bandwidth In 40Mbps, Bandwidth Out 40Mbps. Kompresija snimanja: H.265+; 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 6TB . SMD Plus.

Cijena i dobavlјivost na upit



## XVR5104HS-I3-snimač

VR-372-4

Penta-brid video snimač sa 4 analogna kanala plus 2 dodatnih ip kanala rezolucije do 6MP. AI tehnologija.

Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 32Mbps, Bandwidth Out 32Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## XVR5108HS-I3- snimač

VR-360-4

Penta-brid video snimač sa 8 analogna kanala plus 4 dodatnih IP kanala rezolucije do 6MP. AI tehnologija.

Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 64Mbps, Bandwidth Out 64Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## XVR1B16-I snimač

VR-467

Penta-brid video snimač sa 16 analogna kanala plus 2 dodatna ip kanala rezolucije do 6MP.

Maksimalna rezolucija snimanja 1080N. Frame rate: 1. kanal 1080N (1fps~25/30 fps), ostali 1080N (1fps~15 fps); 960H/D1/HDI/BCIF/CIF (1fps~25/30 fps). Bandwidth In 64Mbps, Bandwidth Out 64Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 16TB. SMD Plus.

Cijena i dobavlјivost na upit



## XVR5116HS-I3 snimac.

VR-361-6

Penta-brid video snimač sa 16 analogna kanala plus 8 dodatnih ip kanala rezolucije do 6MP. AI tehnologija.

Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0, 1x USB 3.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit





## XVR7808S snimač Rasprodaja

VR-402

Penta-brid video snimač sa 8 analognih kanala plus 4 dodatnih IP kanala rezolucije do 5MP.

Maksimalna rezolucija snimanja 2MP. Frame rate: 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps). Bandwidth In 48Mbps. Kompresija snimanja: H.264+/H.264. 1x VGA, 2x HDMI. 8x audio in, 1x audio out. 2x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0, 2x USB 3.0. RS485 komunikacija. 8HDD maksimalnog kapaciteta 8TB po disku.

Cijena i dobavlјivost na upit



## XVR7816S snimač Rasprodaja

VR-408

Penta-brid video snimač sa 16 analognih kanala plus 8 dodatnih IP kanala rezolucije do 5MP.

Cijena i dobavlјivost na upit



## XVR5216AN-I3 snimač

VR-410-5

Penta-brid video snimač sa 16 analognih kanala plus 8 dodatnih IP kanala rezolucije do 6MP.

Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps-10fps); 4M-N/1080P (1fps-15fps). Bandwidth In 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## XVR8816S snimač Rasprodaja

VR-407

Penta-brid video snimač sa 16 analognih kanala plus 48 dodatnih IP kanala rezolucije do 12MP.

Maksimalna rezolucija snimanja 4MP. Frame rate: 1kanal do 9 kanala 4K(1~12/15fps)/4MP (1~15fps), ostali 4MP(1~15fps); 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps). Bandwidth In 256Mbps. Kompresija snimanja: H.264+/H.264. 1x VGA, 2x HDMI. 16x audio in, 1x audio out. 2x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0, 2x USB 3.0. RS232 ; RS485 komunikacija. 8HDD maksimalnog kapaciteta 8TB po disku.

Cijena i dobavlјivost na upit



## XVR5232AN-I3 snimač

VR-475

Penta-brid video snimač sa 32 analognih kanala. AI tehnologija.

Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps-10fps); 4M-N/1080P (1fps-15fps). Bandwidth In 128Mbps, Bandwidth Out 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 10TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## XVR5104HS-4KL-I3 snimač

Penta-brid video snimač sa 4 analogna kanala plus 4 dodatnih IP kanala rezolucije do 8MP. AI tehnologija.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K/N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 64Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

VR-432-4

Cijena i dobavlјivost na upit



## XVR5108HS-4KL-I3 snimač

Penta-brid video snimač sa 8 analogna kanala plus 8 dodatnih IP kanala rezolucije do 8MP. AI tehnologija.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K/N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps, Bandwidth Out 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

VR-433-6

Cijena i dobavlјivost na upit



## XVR5116H-4KL-I3 snimač

Penta-brid video snimač sa 16 analogna kanala plus 16 dodatnih IP kanala rezolucije do 8MP. AI tehnologija.

Maksimalna rezolucija snimanja 8MP. 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K-N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps, Bandwidth Out 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

VR-478

Cijena i dobavlјivost na upit



## XVR5116HE-4KL-I3 snimač

Penta-brid video snimač sa 16 analogna kanala plus 16 dodatnih IP kanala rezolucije do 8MP. AI tehnologija.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K-N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps, Bandwidth Out 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 16x alarm in, 3x alarm out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.

VR-471

Cijena i dobavlјivost na upit



## XVR5216A-4KL-I3 snimač

Penta-brid video snimač sa 16 analogna kanala plus 16 dodatnih IP kanala rezolucije do 8MP. AI tehnologija.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K-N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps, Bandwidth Out 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 4x audio in, 1x audio out. 16x alarm in, 3x alarm out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

VR-434-5

Cijena i dobavlјivost na upit



## XVR5232AN-4KL-I3 snimač

Penta-brid video snimač sa 32 analogna kanala sa AI tehnologijom.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K-N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

VR-463-1

Cijena i dobavlјivost na upit





## XVR5432L-4KL-I3 snimač

VR-481

Penta-brid video snimač sa 32 analogna kanala sa AI tehnologijom.

Maksimalna rezolucija snimanja 8MP. Frame rate: 4K (1fps-7fps); 6MP (1fps-10fps); 5MP (1fps-12fps); 4K-N, 4MP/3MP (1fps-15fps); 4M-N/1080P (1fps-25/30fps). Bandwidth In 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. RS485 komunikacija. 4HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.

Cijena i dobavlјivost  
na upit



## MXVR4104-GFWI mobilni snimač

VR-470

### Mobilni snimač

Digitalni mobilni snimač, 4-kanalni, rezolucija snimanja 2Mpix, mogućnost IP kamera do 1080p rezolucije. Broj fps 25, djeljene ekrana 1/4/8/9, OSD ispis (kanal, vrijeme GPS pozicija), Video kompresija H.265, smart H.265, H.264, smart H.264. Audio kompresija G.711A/G.711 U/PCM.

Mreža: IOS, Android, Wi-Fi (INTEGRISAN 2.4 Wi-Fi modul).

AI funkcije: ADAS (Upozorenja za prednji sudar, napuštanje trake i preblizu udaljenost vozila), DSM (Podržava otkrivanje pospane vožnje, rastresene vožnje, pozivanja tokom vožnje, bez vozača). Hard disk 2.5" SATA, SD kartica 1 (256G). 4 ulaza, two-way talk, podržano, RS-232x2, RS-485x1, USB prednji ulaz 2 kom, zadnji 1 kom. Satelitsko pozicioniranje GPS/GLONASS. Napajanje DC 6-36V. Potrošnja 8.4W. Radna temperatura od -30 °C do +70 °C

Cijena i dobavlјivost  
na upit





## IPC-HFW1230S-0280B-S5 bullet kamera

2MP mrežna kamera u bullet kućištu.

1/2.7" CMOS sa progresivnim skeniranjem. 0.08 Lux@F2.0. Maksimalna rezolucija 1920x1080. Fiksna optika 2,8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje, PoE. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Ugaoni nosač je PFA151 Materijal: Metal i Plastika.

VK-656-2

Cijena i dobavljaljivost na upit



## IPC-HDBW1230E-0280B-S5 kamera

2MP mrežna kamera u dom antivandal kućištu.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.01lux / F2.0 (Color). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. DWDR. Domet IC dioda 30 metara. Napajanje 12VDC /PoE, 5.1W max. Nivo zaštite IP67, IK10, radna temperatura -40 °C do +60 °C. Odgovarajuća baza PFA136, nosač za stub PFB203W + PFA152-E, zidni nosač PFB203W. Materijal: Metal.

VK-740

Cijena i dobavljaljivost na upit



## IPC-HFW2249S-S-IL-0280B kamera

2MP mrežna kamera u bullet kućištu sa Full-color tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux@F1.6. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet LED dioda 30 metara. integrisan mikrofon. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification and accurate detection of vehicle and human). 12v napajanje,PoE. Odgovarajuća dozna je PFA134, 130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-1003

Cijena i dobavljaljivost na upit



## IPC-HDW2249TM-S-IL-0280B kamera

2MP mrežna kamera u eyeball kućištu sa Full-color tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux@F1.6. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet LED dioda 30 metara. integrisan mikrofon. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification and detection of vehicle and human). 12v napajanje,PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Zidni nosač je PFB205W. Materijal: Metal i Plastika.

VK-1063

Cijena i dobavljaljivost na upit



## IPC-HDBW2241E-S-0280B kamera

2MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux @F1.6. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 30 metara. Slot za microSD karticu do 256GB. Integriran mikrofon. Video analitika: Tripwire, intrusion (classification accurate detection of vehicle and human). 12v napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

VK-1057

Cijena i dobavljaljivost na upit



## IPC-HDBW3241E-AS-0280B kamera Rasprodaja

2MP mrežna antivandal kamera sa WizSense tehnologijom u Dom kućištu

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux @F1.6. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8 mm. Kompresija H.264+/H.265+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 50 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification accurate detection of vehicle and human). 12V napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

VK-838

Cijena i dobavljaljivost na upit



## IPC-HDBW1230R-ZS-2812-S5 dom kamera

VK-869

2MP IR varifokalna Dome mrežna kamera

1/2.8 CMOS senzor slike, niska osjetljivost, visoka definicija slike. Rezolucija: 1920x1080 .DWDR. Day/Night (ICR). Motorizovani objektiv 2.8-12mm. Kompresija: H.265+ / H.265 / H.264+ / H.264 / MJPEG. Micro SD slot do 256GB. IR :domet do 40m. Zaštita: IP67, IK10. Napajanje: DC12V, PoE. Odgovarajuća dozna PFA137, nosač za stub PFB203W+152-E, zidni nosač PFB203W. Materijal: metal.

Cijena i dobavlјivost na upit



## IPC-HFW1230T-ZS-2812-S5 bullet kamera

VK-870

2MP mrežna kamera u bullet kućištu

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002Lux/F1.5, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Motorizovana promjenljiva optika 2.7-13.5mm. Kompresija H.265+/H.264+. WDR 120dB. Domet IC dioda 60metara. Integrisan mikrofoni, audio izlaz/lalarmni ulaz/lalarmni izlaz, slot za microSD karticu do 256GB. Video analitika (Perimeter Protection): Tripwire, intrusion (klasifikacija i detekcija vozila i ljudi). Napajanje 12VDC /PoE, 9.9W max. Nivo zaštite IP67, radna temperatura -30 °C do +60 °C. Odgovarajuća baza PFA135/PFA130-E/PFA122, nosač za stub PFA130-E + PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HUM4231S-L5-0280B-S3 kamera

VK-916-2

2MP fiksna Pinhole mrežna kamera

Senzor: 1/3 CMOS. Rezolucija: 1920 X 1080. Kompresija: H265/H.264. Dva strima. WDR: 120dB. Osjetljivost: 0.01 Lux@F2.0 (Color, 30IRE). Fiksni objektiv: 2.8mm. Redukcija šuma: 3D DNR, HLC, BLC. IVS: virtuelna linija, uljez. Audio: lin/out RCA, ugrađen mikrofoni. Cyber Security. Napajanje: DC12V. Potrošnja: 1.6W. Materijal: metal.

Cijena i dobavlјivost na upit



## IPC-HDBW2231R-ZS-27135 kamera

VK-759

2MP IR mrežna kamera u dome kućištu

1/2.8 Starvis™ CMOS senzor sa progresivnim skeniranjem. Rezolucija: 1920x1080. 120db WDR. Motorizovani objektiv 2.7-13.5 mm. Kompresija: H.265/H.264+/MJPEG (Sub Stream). Micro SD slot do 128GB. IR LEDs: domet do 30m. Zaštita: IP67, IK10. Napajanje: DC12V, PoE. Materijal: metal i plastika.

Cijena i dobavlјivost na upit



## IPC-HFW2231T-ZS-27135-S2 kamera

VK-688

2MP mrežna kamera u bullet kućištu sa StarLight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux@F1.5. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 60 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW2241R-ZAS-27135 dom kamera

VK-1011

2MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002Lux/F1.5. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 40 metara. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12v napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit





## IPC-HFW2241T-ZAS kamera

VK-1041

2MP mrežna kamera u bullet kućištu sa StarLight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002 Lux@F1.5 . Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 60 metara. Slot za microSD karticu do 256GB. 1x alarm in, 1x alarm out. 1x audio in, 1x audio out. Video analitika: Tripwire, intrusion (classification and accurate detection of vehicle and human). 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost na upit



## IPC-HFW5241E-ZE kamera

VK-800

2MP mrežna kamera u bullet kućištu sa StarLight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.002Lux/F1.5. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 60 metara. 2x alarm ulaz, 1x alarm izlaz. 1x audio ulaz, 1x audio izlaz. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (Recognition of human and vehicle), Face Capture, People Counting, Object Abandoned/Missing. 12v napajanje, ePoE. Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152-E. Materijal: Metal i Plastika.

Cijena i dobavlјivost na upit



## IPC-HFW5231EP-Z5E kamera

VK-746

2MP IR mrežna kamera u bullet kućištu

1/2.8" STARVIS™ CMOS sa progresivnim skeniranjem. Color: 0.006Lux/F1.4. Maksimalna rezolucija 1920x1080. Motorizovani varifokal 7-35 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LEDs 100 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned/missing, face detection. 12v napajanje, ePoE. Nosač za banderu je PFA152-E. Materijal: Metal

Cijena i dobavlјivost na upit



## IPC-HFW5231E-Z12E-5364 kamera

VK-753

2MP IR mrežna kamera u bullet kućištu

1/2.8" STARVIS™ CMOS sa progresivnim skeniranjem. Color: 0.006Lux/F1.4. Maksimalna rezolucija 1920x1080. Motorizovani varifokal 5.3 - 64 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LEDs 200 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned/missing, face detection. 12v napajanje, ePoE. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost na upit



## IPC-HFW8331EP-Z kamera

VK-598

3MP IR mrežna kamera u bullet kućištu

1/2.8" STARVIS™ CMOS sa progresivnim skeniranjem. Color: 0.005Lux/F1.4. Maksimalna rezolucija 2048x1536. Motorizovani varifokal 2.7-13.5 mm. Kompresija H.265+/H.264/H.264B/H.264H/MJPEG. Nivo zaštite IP67, IK10. 140dB WDR. Domet IR LEDs 50 metara. Slot za micro SD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned/missing, face detection, people counting, heat map. 12v napajanje, PoE. Nosač za banderu je PFA152-E. Materijal: Metal

Cijena i dobavlјivost na upit



## IPC-HFW8331EP-Z5 kamera

VK-642

3MP IR mrežna kamera u bullet kućištu

1/2.8" STARVIS™ CMOS sa progresivnim skeniranjem. Color: 0.005Lux/F1.4. Maksimalna rezolucija 2048x1536. Motorizovani varifokal 7-35 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP66, IK10. 140dB WDR. Domet IR LEDs 100 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned/missing, face detection, people counting, heat map. 12v napajanje, PoE. Nosač za banderu je PFA152. Materijal: Metal

Cijena i dobavlјivost na upit





SLIKA  
TRENUTNO NIJE  
DOSTUPNA

**IPC-HFW2320RP-VFS-IER6 kamera**  
**Rasprodaja**

IPC-HFW2320RP-VFS-IER6

3MP kamera za VF objektivom 60m IR

VK-589

Cijena i dobavljaljivost  
na upit



NOVO

**IPC-HDW1239V-A-IL-0280B**

2MP mrežna kamera u eyeball kućištu sa  
Smart dual light tehnologijom

1/2.8" CMOS sa progresivnim skeniranjem.  
Color: 0.005 Lux@F1.6. Maksimalna rezolucija  
1920x1080. Fiksna optika 2.8mm. Kompresija  
H.265+/H.264+. DWDR. Domet IR/LED dioda  
30 metara. integrisan mikrofon. Nivo zaštite  
IP67. 12v napajanje, PoE. Odgovarajuća dozna  
je PFA13G. Nosač za banderu je PFA152-E.  
Materijal: Metal i Plastika.

VK-1161

Cijena i dobavljaljivost  
na upit



## IPC-HDBW1431E-0280B-S4

VK-741-2

4MP Entry IR fiksna dome mrežna kamera

Rezolucija: 2688x1520. Kompresija: H.265; H.264;H.264B;MJPG .Optika: Fiksna 2.8mm. IR LEDs domet: 30 m. WDR: 120 dB. Napajanje: 12V DC/PoE, max.< 5.5W . Zaštita: IP67, IK10. Dozna: PFA136. Nosač za stub:PFA152-E . Nosač za zid: PFB203W. Materijal metal.

Cijena i dobavlјivost na upit



## IPC-HDBW2441E-S-0280B kamera

VK-1021

4MP IR fiksna WizSense mrežna kamera u dome kućištu

1/2.9" CMOS senzor. Color: 0.006 Lux @ F1.6. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8mm. Kompresija H.265; H.264; H.264H; H.264B; MJPEG. Nivo zaštite IP67, IK10. 120dB WDR. Integrisan mikrofon. Domet IR LEDs 30 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12v napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E,PFA-150. Zidni nosač je PFB203W,PFB305W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW2431E-S-0280B-S2 kamera

VK-841

4MP IR mini dome mrežna kamera

1/3" CMOS senzor. Rezolucija:2688 × 1520. Max IR distance: 30 m. Osvjetljenje: 0.008 Lux @ F1.6. Fiksni objektiv, širina objektivna 2.8 mm. Kompresija: H.264/H.265. WDR 120db. Pametne funkcije: Intrusion, tripwire. Max. 256 GB SD card. Napajanje: 12V DC/POE. Nivo zaštite: IP67, IK10. Materijal:metal.

Cijena i dobavlјivost na upit



## IPC-HFW2449S-S-IL-0280B Full-color Bullet kamera

VK-1006

4MP Full-color Dual-iluminator mrežna kamera u bulit kućištu

1/2.9" CMOS sa progresivnim skeniranjem. Color: 0.006 Lux@F1.6 Maksimalna rezolucija 2688x1520. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. 120dB WDR. Warm light/IR LED diode, domet dioda 30metara. Integrisan mikrofon. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (klasifikacija i detekcija vozila i ljudi). Napajanje 12VDC/PoE, 5.2W max. Nivo zaštite IP67.Odговarajuća baza PFA130-E/PFA134, nosač za stub PFA152-E + PFA130-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDW2449TM-S-IL-0280B

VK-1078

4MP mrežna dual light kamera u eyeball kućištu sa Full-color tehnologijom.

1/2.9 CMOS sa progresivnim skeniranjem. Color 0.006 Lux@F1.6. 4MP (2688 × 1520). Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet iluminatora 30m. Integrisan mikrofon. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification and accurate detection of vehicle and human). 12V napajanje, PoE. Odговarajuća dozna je PFA130-E.Nosač za banderu je PFA152-E. Zidni Nosač je PFB205W-E. Materijal: Metal i Plastika.

Cijena i dobavlјivost na upit



## IPC-HDW1431T-ZS-S4 kamera

VK-852

4MP entry IR varifokalna mrežna kamera u eyeball kućištu

1/3" CMOS sa progresivnim skeniranjem.Rezolucija:2688x1520 pix @25/30 fps. Kompresija: H265/ H.264. Dva strima. WDR: 120dB. Osjetljivost: color: 0.03lux/F1.7.Motorizovani zoom: 2.8-12mm. Redukcija šuma: 3D. Digitalni zum: 16x .Micro SD slot do 256GB IR :domet do 50m. Zaštita: , IP67. Napajanje: DC12V, PoE (802.3af).Potrošnja: 6.9W.Odговarajuća baza PFA137, PFA130, PFB203W, PFB203W + PFA152-E. Materijal:metal.

Cijena i dobavlјivost na upit





## IPC-HFW1431T-ZS-S4 kamera

VK-853

4MP entry IR varifokalna mrežna kamera u bullet kućištu

1/3 CMOS senzor. Rezolucija:2688x1520. WDR 120 dB. Day/Night (ICR). 3DNR . Motorizovani objektiv 2.8-12mm. Kompresija: H265, H.264. Dva strima Osjetljivost: color: 0.03lux/F1.7 , 0Lux (IR on). SD kartica maks. 256 GB . IR LED do 50m. Napajanje: 12Vdc/PoE (802.3af). Potrošnja: maks. 7.4W. Zaštita: IP67. Odgovarajuća baza PFA135, PFA130, PFA130 + PFA152-E.Materijal:metal.

Cijena i dobavlјivost na upit



## IPC-HDBW2431RP-ZS-S2 kamera Rasprodaja

VK-670

4MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/3" CMOS sa progresivnim skeniranjem. Color: 0.008 Lux @ F1.5. Maksimalna rezolucija 2688x1520. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 40 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HFW2441T-ZAS-27135 kamera

VK-1046

4MP IR varifokalna WizSense mrežna kamera u bullet kućištu

1/2.9" CMOS senzor. Color: 0.006 Lux @F1.5. Maksimalna rezolucija 2688x1520. Motorizovani varifokal 2.7-13.5mm. Kompresija H.265; H.264; H.264H; H.264B; MJPEG. Nivo zaštite IP67,IK10. 120dB WDR. Integrisan mikروفon. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (Recognition of vehicle and people). 12v napajanje, ePoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW5442E-ZE-2712-DC12AC24Vkamera

VK-806

4MP pro AI IR varifokalna dome mrežna kamera

Rezolucija: 2688x1520. Starlight: Da. Kompresija: H.265; H.264; H.264H;H.264B;MJPG .Optika: Motorizovana 2.7-12mm. IR domet: 40 m. WDR: 140 dB. Stabilizacija slike: Da .Video analitika: Virtuelna linija;upad;brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi);otkrivanje lutanja;ljudi okupljanje; detekcija parkinga;Brojanje osoba;Detekcija lica;Napušteni objekat, pokretni objekat;Heat mape. Micro SD card (do 256 GB). Audio: 1ch ulaz, 1ch izlaz. Alarm:1 ulaz / 1 izlaz. Napajanje: 12V DC/24V AC/PoE+ (802.3at);ePoE, max. 12.4W. Zaštita: IP67, IK10. Dozna: PFA138. Nosač za stub:PFA152-E . Nosač za zid: PFB211W.

Cijena i dobavlјivost na upit



## IPC-HDW5449H-ASE-D2 0280B kamera

VK-996

4MP mrežna kamera u eyeball kućištu sa Full-color tehnologijom.

1/1.8" CMOS sa progresivnim skeniranjem. Color: 0.0002 Lux@F1.0. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. DWDR. Domet LED dioda 50 metara. integrisan mikروفon.1x alarm in, 1x alarm out. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion, fast moving, loitering detection, people gathering. SMD 3.0. Face detection. People counting. 12v napajanje,PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Ugaoni nosač PFB203W. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HFW7442HP-Z4 kamera

VK-811-1

4MP AI IR bullet mrežna kamera

Rezolucija: 4 MP. Starlight: Da. Tip kućišta: BULLET. Kompresija: H.265;H.264; H.264H; H.264B; MJPG. Optika: Motorizovana 8-32mm. IR domet: 120 m. WDR: 140 dB. Stabilizacija slike: Da. Video analitika: Virtuelna linija;upad;brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi); otkrivanje lutanja; ljudi okupljanje; detekcija parkinga; Detekcija lica, Prepoznavanje lica; Brojanje osoba; Napušteni objekat, pokretni objekat;Micro SD card (do 256 GB); Audio: 1ch ulaz, 1ch izlaz. Alarm:3 ulaz / 2 izlaz. Napajanje: 12V DC/24V AC/PoE+ (802.3at);ePoE, max. 17.3W. Zaštita: IP67, IK10. Nosač za stub:PFA154.

Cijena i dobavlјivost na upit







## IPC-HFW1439TL1-A-IL-0280B

4MP Full-color Dual-iluminator mrežna kamera u bulit kućištu

1/2.9" CMOS sa progresivnim skeniranjem. Color: 0.0006 Lux@F1.6 Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. 120dB WDR. Warm light/IR LED diode, domet dioda 30metara. Integrisan mikrofoni. Video analitika:(detekcija ljudi),Odgovarajuća baza PFA130-E/PFA134, nosač za stub PFA152-E . Nivo zaštite IP67.Napajanje 12VDC/PoE, 2.9W max. Kućište: Metal i plastika

VK-1123

Cijena i dobavljalivost na upit



## IPC-HDW1439V-A-IL-0280B

4MP Full-color Dual-iluminator mrežna kamera u dome kućištu

1/2.9" CMOS sa progresivnim skeniranjem. Color: 0.006 Lux@F1.6 Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. 120dB WDR. Warm light/IR LED diode, domet dioda 30metara. Integrisan mikrofoni. Video analitika:(detekcija ljudi),Odgovarajuća baza PFA136/PFA13G nosač za stub PFA152-E . Nivo zaštite IP67.Napajanje 12VDC/PoE, 2.9W max. Kućište: Metal i plastika

VK-1124

Cijena i dobavljalivost na upit



## IPC-HDW2449T-S-LED-0280B-PRO

4MP mrežna kamera u eyeball kućištu sa WizColor tehnologijom

1/1.8 CMOS sa progresivnim skeniranjem. Color: 0.0005 lux @F1.0. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8mm. Kompresija H.265+, H.264+. WDR 120dB. Domet LED diode 30 metara. Integrisan mikrofoni. Pametne funkcije: IVS i SMD Plus. Slot za microSD do 256GB. Napajanje 12VDC, PoE.Zaštita IP67. Odgovarajuća dozna PFA13G. Zidni nosač PFB205W-E. Nosač za banderu PFA152-E. Materijal: Metal i Plastika

VK-1164

Cijena i dobavljalivost na upit



NOVO

## IPC-HFW2449TL-S-LED-0280B-PRO kamera

4MP mrežna kamera u bulet kućištu sa WizColor tehnologijom

1/1.8 CMOS sa progresivnim skeniranjem. Color: 0.0005 lux @F1.0. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8mm. Kompresija H.265+, H.264+. WDR 120dB. Domet LED diode 50 metara. Integrisan mikrofoni. Pametne funkcije: IVS i SMD Plus. Slot za microSD do 256GB. Napajanje 12VDC, PoE.Zaštita IP67. Odgovarajuća dozna PFA130-E/PFA134. Nosač za banderu PFA152-E. Materijal: Metal

VK-1159

Cijena i dobavljalivost na upit

NOVO Nov proizvod



Proizvod u dolasku



Pozovite za više informacija o raspoloživosti



## IPC-HDBW3541F-AS-M-0280B kamera Rasprodaja

VK-861

5MP IR vodo-otporna i anti-vandal WizSense mrežna kamera u dome kućištu

1/2.7" CMOS sa progresivnim skeniranjem. Kompresija H.265/H.264/MJPEG. Rezolucija( 2592Hx1944V) 20fps@ 5Mpix, 25/30 fps/3Mpix. Min.osvjetljenje: 0.005 Lux/F1.6 Color), 0Lux/ F2.0 (IR on). WDR 120dB. Fiksna optika 2.8 mm. IR -8 LEDs do 30 m. SD kartica maks. 256 G.Ethernet: RJ45 (10/100 Base-T). Napajanje: DC12V, PoE (802.3af) Potrošnja: Max 5.7W. Radni temper. opseg: -40°C~+60°C. Zaštita: IP67, IK10.Odgovarajuća baza PFA139, PFB204W, PFA152-E

Cijena i dobavlјivost na upit



## IPC-HFW2549S-S-IL-0280B

VK-1096

5MP fiksna Dual Light WizSense mrežna kamera u bullet kućištu

1/2.7" CMOS senzor. Color: 0.007 Lux@F1.6 . Maksimalna rezolucija 2960x1668. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IR LED 30 metara.Integriran mikrofون. Slot za microSD karticu do 256GB.Video analitika: Tripwire, intrusion,SMD Plus . 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E, PFA134. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost na upit



## IPC-HDBW2541E-S-0280B 5MP dom kamera sa fiksnim objektivom

VK-985

5MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ F1.6. Maksimalna rezolucija 2592x1944. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 30 metara. Integriran mikrofون. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification and detection of vehicle and human). 12v napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW3541E-AS-0280B kamera Rasprodaja

VK-837

5MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux@F1.6. Maksimalna rezolucija 2592x1944. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 50 metara. 1x alarm in, 1x alarm out. 1x audio in, 1x audio out. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (Recognition of human and vehicle). 12v napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HFW5541E-SE-0360 kamera

VK-847

5MP IR fiksna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS senzor. Rezolucija: 2592x 1944. WDR 120 dB. Kompresija:H.265+,H.264+. Osjetljivost : 0.005 lux@F1.6 (Color, 30IRE). SD kartica maks. 256 GB. Fiksni objektiv 3.6mm. IR LED do 50m. Napajanje: 12Vdc/PoE(802.3af). Potrošnja: maks. 6.8W. Zaštita: IP67. Materijal:metal i plastika.

Cijena i dobavlјivost na upit



## IPC-HFW5541E-ASE-0280B-S3 kamera

VK-1068

5MP IR fiksna WizMind mrežna kamera u bullet kućištu

1/2.7" CMOS ssenzor. Color: 0.0009 Lux@F1.6 . Maksimalna rezolucija 2960x1668. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. 1x alarm in, 1x alarm out. 1x audi in, 1x audio out. Domet IR LEDs 50 metara. Slot za microSD karticu do 512GB. Video analitika: Tripwire, intrusion (classification and detection of vehicle and human). 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost na upit





## IPC-HDBW5541R-ASE-0280B-S3 kamera

VK-844-2

5MP IR fiksna WizMind mrežna kamera u dome kućištu

1/2.7" CMOS senzor. Color: 0.0009 Lux @ F1.6. Maksimalna rezolucija 2960x1668. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LEDs 50 metara. Integriran mikrofoni. Slot za microSD karticu do 512GB. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12V napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA156. Zidni nosač je PFB203W/PFB206W. Materijal: Metal.

Cijena i dobavljaljivost na upit



## IPC-HDBW5541R-ASE-0280B-S3-BLACK kamera

VK-844-3

5MP IR fiksna WizMind mrežna kamera u dome kućištu

1/2.7" CMOS senzor. Color: 0.0009 Lux @ F1.6. Maksimalna rezolucija 2960x1668. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LEDs 50 metara. Integriran mikrofoni. Slot za microSD karticu do 512GB. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12V napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA156. Zidni nosač je PFB206W. Materijal: Metal.

Cijena i dobavljaljivost na upit



## IPC-HFW5541T-ASE-0280B-S3 kamera

VK-839-3

5MP IR fiksna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS senzor. Rezolucija: 2960x 1668. Kompresija: H.265; H.264; H.264H; H.264B; MJPEG. Fiksna optika: 2.8 mm. IR LEDs domet: 80 m. WDR: 120 dB. Video analitika: Virtuelna linija; upad; brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi); otkrivanje lutanja; ljudi okupljanje; detekcija parkinga; Micro SD card (do 512 GB); Audio: 1ch ulaz, 1ch izlaz. Alarm: 1 ulaz / 1 izlaz. Napajanje: DC 12V, PoE (802.3af), 9.8W. Zaštita: IP67, IK10. Dozna: PFA130-E. Nosač za stub: PFA152-E.

Cijena i dobavljaljivost na upit



## IPC-HFW5541T-ASE-0360B-S3 kamera

VK-839-2

5MP IR fiksna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS senzor. Rezolucija: 2960x 1668. Kompresija: H.265; H.264; H.264H; H.264B; MJPEG. Fiksna optika: 3.6 mm. IR LEDs domet: 80 m. WDR: 120 dB. Video analitika: Virtuelna linija; upad; brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi); otkrivanje lutanja; ljudi okupljanje; detekcija parkinga; Micro SD card (do 512 GB); Audio: 1ch ulaz, 1ch izlaz. Alarm: 1 ulaz / 1 izlaz. Napajanje: DC 12V, PoE (802.3af), 9.8W. Zaštita: IP67, IK10. Dozna: PFA130-E. Nosač za stub: PFA152-E.

Cijena i dobavljaljivost na upit



## IPC-HDBW2531R-ZS-S2 kamera

VK-745

5MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.008 Lux @ F1.5. Maksimalna rezolucija 2592x1944. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 40 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavljaljivost na upit



## IPC-HFW2531T-ZS-27135-S2 kamera

VK-711

5MP mrežna kamera u bullet kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.008 Lux@F1.5. Maksimalna rezolucija 2592x1944. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 60 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavljaljivost na upit





## IPC-HFW3549T1-AS-PV-0280B-S3 Full-color Bullet kamera

5MP Full-color Dual-iluminator Active Deterrence mrežna kamera u bullet kućištu

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.003 Lux@F1.0. Maksimalna rezolucija 2592x1944. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. 120dB WDR. Warm light/IR LED diode, doomet dioda 30metara. Integrisan dualni mikrofoni, sirena, zvučnik i crveno-plavi blicer. Alarmni ulaz/lalarmni izlaz, audio ulaz/audio izlaz (podržava two-way talk - dvosmjernu komunikaciju), slot za microSD karticu do 256GB. Video analitika (Perimeter Protection): Tripwire, intrusion (klasifikacija i detekcija vozila i ljudi). Napajanje 12VDC/PoE, 9.7W max. Nivo zaštite IP67. Odgovarajuća baza PFA135, PFA130-E, nosač za stub PFA130-E + PFA152-E. Materijal: Metal i plastika.

VK-979

Cijena i dobavljaljivost na upit



## IPC-HDW3549H-AS-PV-0280B-S3 kamera

5MP Full-color Dual-iluminator Active Deterrence mrežna kamera u eyeball kućištu

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.003 Lux@F1.0. Maksimalna rezolucija 2592x1944. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. 120dB WDR. Warm light/IR LED diode, doomet dioda 30metara. Integrisan dualni mikrofoni, sirena, zvučnik i crveno-plavi blicer. Alarmni ulaz/lalarmni izlaz, audio ulaz/audio izlaz (podržava two-way talk - dvosmjernu komunikaciju), slot za microSD karticu do 256GB. Video analitika (Perimeter Protection): Tripwire, intrusion (klasifikacija i detekcija vozila i ljudi). Napajanje 12VDC/PoE, 8.8W max. Nivo zaštite IP67, radna temperatura -40 °C do +60 °C. Odgovarajuća baza PFA137, PFA130-E, nosač za stub PFB203W + PFA152-E, zidni nosač PFB203W/ PFB205W. Materijal: Metal.

VK-875-1

Cijena i dobavljaljivost na upit



## IPC-HFW2541T-ZAS-27135-S2 kamera

5MP IR varifokalna WizSense mrežna kamera u bullet kućištu

1/2.7 CMOS senzor. Rezolucija: 2960x 1668. Kompresija: H.265; H.264; H.264H; H.264B; MJPEG. Motorizovani varifokal: 2.7-13.5 mm. IR LEDs doomet: 60 m. WDR: 120 dB. Video analitika: tripwire, intrusion. Micro SD card (do 256 GB); Napajanje: DC 12V, PoE (802.3af). Zaštita: IP67. Dozna: PFA130-E. Nosač za stub: PFA152-E. Materijal: metal.

VK-1007-1

Cijena i dobavljaljivost na upit



## IPC-HFW2541T-ZAS-27135 kamera

5MP mrežna kamera u bullet kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux@F1.5. Maksimalna rezolucija 2592x1944. Varifokalna optika 2.7 - 13.5 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. 1x alarm in, 1x alarm out. 1x audi in, 1x audio out. Doomet IC dioda 60 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E, PFA135. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-1007

Cijena i dobavljaljivost na upit



## IPC-HFW5541E-Z5E-0735 kamera

IPC-HFW5541E-Z5E

5MP IR varifokalna WizMind mrežna kamera u bullet kućištu, 1/2.7 CMOS senzor. Rezolucija: 2960x 1668. WDR 120 dB. Kompresija: H.265+, H.264+. Osjetljivost : 0.0009 lux@F1.5 (Color, 30IRE). Pametne detekcije: Virtuelna linija, upad, brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi), otkrivanje lutanja, ljudi okupljanje, detekcija parkinga, Detekcija lica, Brojanje osoba, Nestali / uklonjeni objekat. Audio: 1ch ulaz, 1ch izlaz. Alarm: 2 ulaz / 1 izlaz. SD kartica maks. 512 GB. Motorizovani objektiv 2.7 ~13.5mm. IR LED do 60m. Napajanje: 12Vdc/PoE(802.3af). Zaštita: IP67, IK10. Odgovarajuća baza PFA121. Materijal: metal.

VK-938

Cijena i dobavljaljivost na upit



## IPC-HFW5541E-ZE-27135 kamera

5MP IR varifokalna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS sa progresivnim skeniranjem. Rezolucija: 2592x 1944. WDR 120 dB. Kompresija: H.265, H.264. Osjetljivost : 0.005 lux@F1.5 (Color, 30IRE). Pametne detekcije: Virtuelna linija, upad, brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi), otkrivanje lutanja, ljudi okupljanje, detekcija parkinga, Detekcija lica, Brojanje osoba, Nestali / uklonjeni objekat. Audio: 1ch ulaz, 1ch izlaz. Alarm: 1 ulaz / 1 izlaz. SD kartica maks. 256 GB. Motorizovani objektiv 2.7 ~13.5mm. IR LED do 60m. Napajanje: 12Vdc/PoE(802.3af). Potrošnja: maks. 10.9W. Zaštita: IP67, IK10. Odgovarajuća baza PFA121 za zid, PFA121 + PFA152-E za stub.

VK-934

Cijena i dobavljaljivost na upit



## IPC-HDBW5541E-ZE-27135-DC12AC24V S3 kamera

VK-1062

5MP IR varifokalna WizMind mrežna kamera u dome kućištu

1/2.7" CMOS senzor. Color: 0.0009 Lux @ F1.5. Maksimalna rezolucija 2960x1668. Motorizovani varifokal 2.7-13.5mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LEDs 40 metara. Integrisan mikrofoni. Slot za microSD karticu do 512GB. Video analitika: Tripwire, intrusion (classification detection of vehicle and human). 12v napajanje, PoE. Odgovarajuća dozna je PFA138. Nosač za banderu je PFA156. Zidni nosač je PFB211W. Materijal: Metal.

Cijena i dobavljaljivost na upit



## IPC-HFW5541E-ZE-27135-S3 buet kamera

VK-934-1

5MP IR varifokalna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS sa progresivnim skeniranjem. Rezolucija: 2592x 1944. WDR 120 dB. Kompresija:H265+,H.264+. Osjetljivost : 0.005 lux@F1.5 (Color, 30IRE). Pametne detekcije: Virtuelna linija, upad, brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi), otkrivanje lutanja, ljudi okupljanje, detekcija parkinga, Detekcija lica, Brojanje osoba, Nestali / uklonjeni objekat. Audio: 1ch ulaz, 1ch izlaz. Alarm:2 ulaz / 1 izlaz .SD kartica maks. 256 GB. Motorizovani objektiv 2.7 ~13.5mm. IR LED do 50m. Napajanje: 12Vdc/PoE(802.3af). Potrošnja: maks. 10.9W. Zaštita: IP67, IK10.Materijal:metal i plastika.

Cijena i dobavljaljivost na upit




## IPC-HFW5541E-ZE-0735-S3 kamera bulit 5MP

VK-938-1

5MP IR varifokalna WizMind mrežna kamera u bullet kućištu

1/2.7 CMOS senzor. Rezolucija: 2960x 1668. WDR 120 dB. Kompresija: H265+, H.264+. Osjetljivost : 0.0009 lux@F1.5 (Color, 30IRE). Pametne detekcije: Virtuelna linija, upad, brzo kretanje (tri funkcije podržavaju klasifikaciju i tačnu detekciju vozila i ljudi), otkrivanje lutanja, ljudi okupljanje, detekcija parkinga, Detekcija lica, Brojanje osoba, Nestali / uklonjeni objekat. Audio: 1ch ulaz, 1ch izlaz. Alarm:2 ulaz / 1 izlaz .SD kartica maks. 512 GB.Motorizovani objektiv 2.7 ~13.5mm. IR LED do 60m. Napajanje: 12Vdc/PoE(802.3af). Zaštita: IP67, IK10.Odgovarajuća baza PFA121.Materijal:metal.

Cijena i dobavljaljivost na upit



## IPC-HDW2549TM-S-IL-0280B kamera

VK-1089

5MP fiksna Dual Light WizSense mrežna kamera u eyeball kućištu

1/2.7" CMOS senzor. Color: 0.007 Lux@F1.6 . Maksimalna rezolucija 2960x1668. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IR LED 30 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E, PFB205W-E. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavljaljivost na upit




## IPC-HDBW2541E-S-0280B-S2 kamera

VK-985-1

5MP mrežna kamera u dome kućištu sa StarLight tehnologijom.

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ F1.6. Maksimalna rezolucija 2592x1944. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 30 metara. Integrisan mikrofoni. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion (detekcija covjevoziolo),SMD Plus. 12v napajanje,PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavljaljivost na upit



## IPC-HFW1639TC-A-IL-0280B-S6

VK-1132

6MP Full-color Dual-iluminator mrežna kamera u bulit kućištu

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.007 Lux@F1.6  
Maksimalna rezolucija 3200x1800. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. DWDR. Warm light/IR LED diode, domet dioda 30metara. Integrisan mikrofon. Video analitika:(detekcija ljudi).Odgovarajuća baza PFA130-E, nosač za stub PFA152-E . Nivo zaštite IP67.Napajanje 12VDC/PoE, 2.9W max. Kućište: Metal

Cijena i dobavlјivost na upit



## IPC-HDW1639T-A-IL-0280B-S6

VK-1149

6MP Full-color Dual-iluminator mrežna kamera u dome kućištu

1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.007 Lux@F1.6  
Maksimalna rezolucija 3200x1800. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. DWDR. Warm light/IR LED diode, domet dioda 30metara. Integrisan mikrofon. Video analitika:(detekcija ljudi).Odgovarajuća baza PFA13A-E/PFB204W, nosač za stub PFA152-E . Nivo zaštite IP67.Napajanje 12VDC/PoE, 5.3W max. Kućište: Metal

Cijena i dobavlјivost na upit





### IPC-HFW5830E-Z5 kamera Rasprodaja

8MP IR mrežna kamera u bullet kućištu

1/2.5" CMOS senzor sa progresivnim skeniranjem. Color: 0.05 Lux@F1.6. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 7 - 35 mm. Kompresija H.265+ /H.264+. Nivo zaštite IP67, IK10. Domet IR LED 100 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned, face detection. 12v napajanje, PoE. Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152. Materijal: Metal.

VK-647

Cijena i dobavlјivost na upit



### IPC-HFW2849S-S-IL-0280B kamera

8MP fiksna WizSense mrežna kamera u bullet kućištu

1/2.7" CMOS senzor. Color: 0.008 Lux@F1.6. Rezolucija 3840 × 2160. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet iluminatora 30 metara. Ima integrisan mikrofون. Slot za microSD karticu do 256GB. Video analitika Tripwire, intrusion (sa klasifikacijom i detektovanjem ljudi i vozila). 12V napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-1061

Cijena i dobavlјivost na upit



### IPC-HFW2831S-S-0280B-S2 bulet kamera

8 MP lite IR fiksna mrežna kamera u bullet kućištu

1/2.7" CMOS senzor. Color: 0.008 Lux@F1.6. Rezolucija 3840 × 2160. Fiksna optika 2.8mm. Kompresija H.265; H.264; H.264B; MJPEG. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LED 30 metara. Slot za microSD karticu do 256GB. Video analitika Tripwire, intrusion. 12V napajanje, PoE. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-952

Cijena i dobavlјivost na upit



### IPC-HDBW3841E-AS-0280B-S2 8MP dom kamera sa fiksnim objektivom

8MP IR fiksna WizSense mrežna kamera u dome kućištu

1/2.8" CMOS senzor. Color: 0.008 Lux@F1.5. Maksimalna rezolucija 3840x2160. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LED 30 metara. Slot za microSD karticu do 256GB. Ima integrisan mikrofون. Audio 1 in, 1 out; alarm 1 in, 1 out. Video analitika: Tripwire, Intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

VK-904

Cijena i dobavlјivost na upit



### IPC-HFW3841E-AS-0360B-S2 kamera

8MP IR fiksna WizSense mrežna kamera u bullet kućištu

1/2.8" CMOS senzor. Color: 0.007 Lux@F1.4. Maksimalna rezolucija 3840x2160. Fiksna optika 3.6mm. Kompresija H.264+/H.265+. Nivo zaštite IP67. 120dB WDR. Domet IR LED 30 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA130-E. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-889-1

Cijena i dobavlјivost na upit



### IPC-HDBW2831R-ZS-27135-S2 kamera Rasprodaja

8MP lite IR varifokalna mrežna kamera u dome kućištu

1/2.7" CMOS senzor. Color: 0.008 Lux@F1.5. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7-13.5mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LED 40 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, Intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

VK-954

Cijena i dobavlјivost na upit



## IPC-HDW2831T-ZS-27135-S2 kamera

VK-1005

8MP lite IR varifokalna mrežna kamera u eyeball kućištu

1/2.7" CMOS senzor. Color: 0.008 Lux@F1.5. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7-13.5mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. 120dB WDR. Domet IR LED 40 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, Intrusion detection. 12v napajanje, PoE. Odgovarajuća dozna je PFA137/PFA130-E. Nosač za stub je PFA152-E. Zidni nosač je PFB203W-E. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW3841R-ZAS-27135

VK-896

8MP IR varifokalna WizSense mrežna kamera u dome kućištu

1/2.8" CMOS senzor. Color: 0.007 Lux@F1.5. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7-13.5 mm. Kompresija H.264+/H.265+. Nivo zaštite IP67,IK10. 120dB WDR. Domet IR LED 40 metara. Slot za microSD karticu do 256GB. Audio 1 in,1 out;alarm 1 in,1 out.Video analitika: Tripwire, Intrusion. 12v napajanje, PoE. Odgovarajuća dozna je PFA137. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HFW5831EP-ZE kamera

VK-747

8MP IR mrežna kamera u bullet kućištu

1/2.5" STARVIST™ CMOS senzor sa progresivnim skeniranjem. Color: 0.05 Lux@F1.4 . Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7 - 12mm. Kompresija H.265+ /H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LED 50 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned,face detection.12v napajanje, PoE. Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost na upit



## IPC-HDBW5831E-ZE-2712 dome kamera

VK-1029-D

8MP IR mrežna kamera u dome kućištu

1/2.5" STARVIST™ CMOS sa progresivnim skeniranjem. Color: 0.05 Lux@F1.4. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7-12mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67,IK10. 120dB WDR. Domet IR LED 50 metara. Audio 1 in,out;alarm 1 in, 1 out. Slot za microSD karticu do 256GB. Video analitika: Tripwire, Intrusion detection, object abandoned,face detection.12v napajanje, PoE. Odgovarajuća dozna je PFA138. Nosač za banderu je PFA152-E. Zidni nosač je PFB302S. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HDBW3849R1-ZAS-PV-27135 kamera

VK-1024-D

8MP Active Deterrence varifokalna WizSense mrežna kamera u dome kućištu

1/2.8" CMOS senzor. Color: 0.004 Lux@F1.0. Maksimalna rezolucija 3840x2160. Motorizovani varifokal 2.7-13.5mm. Kompresija H.265+/H.264+. Nivo zaštite IP67,IK10. 120dB WDR. Domet IR LED 50 metara. Audio 1 in,1out;alarm 1 in, 1 out. Slot za microSD karticu do 256GB. Video analitika: Tripwire, Intrusion detection. 12v napajanje, PoE. Odgovarajuća dozna je PFA197R. Nosač za banderu je PFA156. Zidni nosač je PFB206W. Materijal: Metal.

Cijena i dobavlјivost na upit



## IPC-HFW5831E-Z5E kamera

VK-713

8MP IR mrežna kamera u bullet kućištu

1/2.5" CMOS senzor sa progresivnim skeniranjem. Color: 0.05 Lux@F1.4 . Maksimalna rezolucija 3840x2160. Motorizovani varifokal 7 - 35mm. Kompresija H.265+ /H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IR LED 100 metara. Slot za microSD karticu do 128GB. Video analitika: Tripwire, intrusion, object abandoned,face detection.12v napajanje, PoE. Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost na upit







## IPC-HFW5842E-Z4E-0832-S2 bulet kamera

VK-955

8 MP IR varifokalna WizMind mrežna kamera u bullet kućištu

1/1.8" CMOS senzor. Color: 0.004 Lux@F1.4 . Maksimalna rezolucija 3840x2160. Motorizovani varifokal 8 - 32 mm. Kompresija H.265+ /H.264+. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 120 metara. Slot za microSD karticu do 256GB. Video analitika: Tripwire, intrusion, face detection, missing object, people counting. 12v napajanje, PoE. Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost  
na upit



## IPC-HFW5842E-ZE-0832-S3

VK-1167

8 MP IR varifokalna WizMind mrežna kamera u bullet kućištu

1/1.8" CMOS senzor. Color: 0.0008 lux@F1.8 . Maksimalna rezolucija 3840x2160. Motorizovani varifokal 8 - 32 mm. Kompresija H.265+ /H.264+. 120dB WDR. Domet IC dioda 60 metara. Integrisan mikrofون. Audio 1 ulaz; 1 izlaz. Alarm 2 ulaza; 2 izlaza Video analitika: AcuPick Tripwire, intrusion, face detection, missing object, people counting, SMD 3.0. 12v napajanje, ePoE. Slot za microSD karticu do 1TB. Nivo zaštite IP67, IK10 Odgovarajuća dozna je PFA121. Nosač za banderu je PFA152-E. Materijal: Metal .

Cijena i dobavlјivost  
na upit





## IPC-EB5541-AS fisheye kamera

5MP WizMind fisheye antivandal mrežna kamera

5MP, 1/2.7" CMOS senzor, maksimalna rezolucija 2592x1944px @25/30 fps, objektiv 1.4mm, ugao gledanja 180°, ROI, SMART H.264+/H.265+, 120dB WDR, 3D DNR, HLC, BLC, detekcija upada, tripwire, brojanje ljudi u izabranom prostoru, heat map za brojanje ljudi, detekcija pokreta, video tampering, alarmni ulaz/izlaz 1/1, audio ulaz/izlaz 1/1, slot za microSD karticu do 256GB, IP67, IK10. Materijal: Metal.

VK-972

PROJEKTNI MODEL



## IPC-PFW8601P-A180-panoramska kamera Rasprodaja

3x2MP multisenzor panoramska mrežna IR Bullet kamera

3 x 1/2.8 STARVIS™ CMOS progresivno skeniranje. Efektivno piksela : 4096 x 832. WDR 120 db. Min. osvjetljenje: 0.007 lux/F1.8. IR rastojanje: do 30 m. Žična daljina: 3.6 mm. 1/1 audio ulaz/ izlaz. 2/1 alarm ulaz/izlaz. Mikro SD slot od 128 GB. Priključak: RJ45 (Ethernet). Video kompresija: H.265/H.264/MJPEG. Intiligentne funkcije IVS (Tripwire, intrusion, missing/abandoned, face detect, people counting, heat map, E-PTZ). Napajanje: PoE /AC24V. Zaštita: IP67, Antivandal IK10. Odgovarajuća baza PFA120, PFA120 + PFA150, PFA120 + PFA151. Materijal: metal.

VK-623

Cijena i dobavlјivost na upit



## IPC-EBW81230P 12Mpix fisheye kamera

12MP panoramska mrežna IR fisheye kamera

1/2.3" CMOS senzor sa progresivnim skeniranjem. Rezolucija: 4000 x 3000. Min. osvjetljenje 0.01Lux/F2.2(Color), 0Lux/F2.2(IR on), 1.57mm fiksni objektiv, IR domet 10m, 3DNR, 1/1 channel In/Out(integrisan mikrofon). Mikro SD slot 128 GB. Napajanje DC12V, PoE (802.3af) <13W. Nivo zaštite: IP67, IK10. Odgovarajuća baza PFA100 Mount Adapter + PFB302S Wall Mount, PFA100 Mount Adapter + PFB302S Wall Mount + PFA152 Pole Mount, PFA105 Mount Adapter + PFA110 Mount Adapter + PFB300C Ceiling Mount.

VK-510-1

Cijena i dobavlјivost na upit



## ITC413-PW4D-IZ1 kamera

4MP mrežna ANPR kamera u bullet kućištu.

1/1.8 CMOS senzor sa progresivnim skeniranjem. Maksimalne rezolucije 2688x1520. Varifokalna optika 2.7mm - 12mm. Detekcija vozila: 3m-6m Kompresija H.265/H.264. Nivo zaštite IP67. 140dB WDR. Domet IC dioda 10 metara. 2x alarm in, 2x alarm out. 1x audio in, 1x audio out; ugradjen mikrofon. Slot za microSD karticu do 128GB. Napajanje 12V, PoE+. Materijal: Metal i Plastika.

VK-1104

Cijena i dobavlјivost na upit



## ITC237-PW6M-IRLZF1050-B Rasprodaja

2MP mrežna ANPR kamera u bullet kućištu.

1/1.8 CMOS senzor sa progresivnim skeniranjem. Maksimalne rezolucije 1920x1080. Varifokalna optika 10mm - 50mm. Detekcija vozila: 8m-30m Kompresija H.265/H.264. Nivo zaštite IP67. 96dB WDR. Domet IC dioda 25 metara. 1x alarm in, 2x alarm out. 1x audio in, 1x audio out. Slot za microSD karticu do 64GB. Napajanje 12V DC, 24V AC, PoE+. Materijal: Metal i Plastika.

VK-622-2-S

Cijena i dobavlјivost na upit



## ITC413-PW4D-IZ3

4MP kamera za prepoznavanje registarskih tablica

1/1.8 CMOS senzor. Rezolucija: 2688x1520. Motorizovani objektiv 8-32mm. Kompresija: H.265, H.264. MJPEG Dva strima. SD kartica maks. 256 GB WDR-140db. IR LED do 8m. Napajanje: 12Vdc/PoE (802.3af). Potrošnja: maks. <20W. Zaštita: IP67 & IK10. Materijal: aluminium i plastika.

VK-1111

Cijena i dobavlјivost na upit



## ITC437-PW6M-IZ-GN kamera Rasprodaja

VK-957

4MP mrežna ANPR kamera u bullet kućištu.

1/1.8 CMOS senzor sa progresivnim skeniranjem. Maksimalne rezolucije 2688x1520. Varifokalna optika 10mm - 50mm. Detekcija vozila:8m-30m Kompresija H.265/H.264. Nivo zaštite IP67. 96dB WDR. Domet IC dioda 30 metara. 3x alarm in, 3x alarm out. 1x audio in, 1x audio out. Slot za microSD karticu do 128GB. Napajanje 12V DC, 24V AC, PoE+. Materijal: Metal i Plastika.

Cijena i dobavlјivost  
na upit



## IPMECS-2234-IZ

VK-1135

Kit Access ANPR sa AI bullet kamerom za prepoznavanje registarskih tablica

CMOS senzor 1/1.8", rezolucija 4 MP na 25fps, H.265 kompresija, motorizovana optika 2.7-12 mm, IR osvetljenje na 850 nm dometa 8 m, domet za čitanje registarskih tablica 2.5-6 m, širina prepoznatog prolaza 3-4 m, maksimalna prepoznata brzina 60 km/h, 1 LAN port 100/1000 Mbps, 2 RS485 porta, 3 ulaza i 2 izlaza za alarme, 1 ulaz i 1 izlaz za audio, WDR 140 dB, prepoznavanje vozila, video metapodaci, OSD, TF kartica slot (maks. 256 GB), LED displej 64x64, IP54 zaštita, napajanje 100-240 Vac <70 W.

Cijena i dobavlјivost  
na upit



**SLIKA  
TRENUTNO NIJE  
DOSTUPNA**

## IPC-H4A-0360B

VK-1118

4MP Wi-Fi pokretna P&T kamera

1/3" 4MP CMOS. Rezolucija 2560x1440. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, abnormal sound alarm, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena. Kompresija H.265/H.264. Wi Fi 50m domet na otvorenom, 1x100Mbps Ethernet Port. Smart Tracking, 16x digital zoom, 0~355° Pan & -5~80° Tilt. Noćna vidljivost do 10 m. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. Napajanje 5VDC, 1A, adapter dolazi uz kameru, radna temperatura -10°C do +45°C. Materijal plastika.

Cijena i dobavlјivost  
na upit



## IPC-F2C-PV-0280B

VK-1116

2MP mrežna Wi-Fi kamera u bullet kućištu.

1/3" CMOS sa progresivnim skeniranjem. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265/H.264. DWDR. Domet IC i LED dioda 30 metara. AI Human Detection, Integrisan mikrofoni zvučnik. Slot za microSD karticu do 256GB. 12v napajanje. Nivo zaštite IP67. Kućište: Metal i plastika

Cijena i dobavlјivost  
na upit



## IPC-F4C-PV-0280B

VK-1117

4MP mrežna Wi-Fi kamera u bullet kućištu.

1/3" CMOS sa progresivnim skeniranjem. Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265/H.264. DWDR. Domet IC i LED dioda 30 metara. AI Human Detection, Integrisan mikrofoni zvučnik. Slot za microSD karticu do 256GB. 12v napajanje. Nivo zaštite IP67. Kućište: Metal i plastika

Cijena i dobavlјivost  
na upit




## IPC-HFW1230DS-SAW-0280B kamera

VK-968

2MP mrežna Wi-Fi kamera u bullet kućištu.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.025Lux / F2.0 (Color), 0 Lux Illumination on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integrisan mikrofoni. Slot za microSD karticu do 256GB. 12v napajanje. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

Cijena i dobavlјivost  
na upit



## IPC-P5B-PV

VK-1122

5 MP WI-FI pokretna PT kamera

1/3" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, detekcija vozila, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB. Kompresija H.265. Smart Full Color, noćna vidljivost do 30 m. Slot za Micro SD karticu do 256GB. Dualna antena 120m domet na otvorenom, 1x100Mbps Ethernet Port. Napajanje 12V, 1A. Nivo zaštite IP66 - Materijal plastika.

Cijena i dobavlјivost  
na upit



## IPC-HDBW1230DE-SW-0280B kamera

VK-987

2MP mrežna Wi-Fi kamera u dome kućištu.

1/3" CMOS sa progresivnim skeniranjem. Color: 0.025 Lux / F2.0 (Color). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. Slot za microSD karticu do 256GB. 12v napajanje dolazi sa kamerom. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

Cijena i dobavlјivost  
na upit





## IPC-HFW1430DS-SAW-0280B Wi Fi kamera

4MP mrežna Wi-Fi kamera u bullet kućištu.

1/3" CMOS sa progresivnim skeniranjem. Color: 0.025 Lux @F2.0 (Color, 30 IRE). Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integriran mikrofoni. Slot za microSD karticu do 256GB. 12v napajanje dolazi sa kamerom. Odgovarajuća dozna je PFA134. Nosač za banderu je PFA152-E. Materijal: Metal.

VK-983

Cijena i dobavljalivost na upit



## SD-P5AE-PV-0400B

5MP Wi-Fi pokretna P&T kamera full color

1/2.8" CMOS senzor. Wi-Fi: IEEE802.11b/g/n, Dual Antena 120m Open Field. Domet IR-a 30 m. Fiksni objektiv 4mm. Video kompresija H.265+/H.264+. Integrirani mikrofoni. SD kartica max 256GB. Rotacija kamere 345°. Motion detekcija, detekcija ljudi, Auto tracking, IVS. Napajanje 12V 1A, (dolazi uz kameru). Plastično kućište. Radna temperatura -30°C~+55°. IP66. Access by a cloud (P2P), podržava Android i iPhone: besplatna aplikacija DMSS.

VK-1120

Cijena i dobavljalivost na upit



## IPC-HDBW1430DE-SW-0280B Wi Fi dome kamera

4MP mrežna Wi-Fi kamera u dome kućištu.

1/3" CMOS sa progresivnim skeniranjem. Color: 0.025 Lux @F2.0 (Color, 30 IRE). Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. Slot za microSD karticu do 256GB. 12v napajanje dolazi sa kamerom. Odgovarajuća dozna je PFA136. Nosač za banderu je PFA152-E. Zidni nosač je PFB203W. Materijal: Metal.

VK-973

Cijena i dobavljalivost na upit



## IPC-SD2A500HB-GN-A-PV-0400-S2 full kolor PT kamera

VK-1052

5MP mrežna kamera u PT kućištu sa Full Color tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (iluminator on). Maksimalna rezolucija 2560x1900. Fiksna optika 4mm. Kompresija H.265/H.264. Nivo zaštite IP66. DWDR. Domet IR/LED dioda 30 metara. Slot za microSD karticu do 512GB. Integriran mikrofoni i zvučnik. Zvučna i svetlosna signalizacija. Video analitika: tripwire, intrusion detection, human detection. Napajanje 12VDC, 1.5A.

Cijena i dobavlјivost na upit



## IPC-SD2A500HB-GN-AW-PV-0400-S2 kamera

VK-1081

5 MP PT Full-color Wi-Fi Dual-iluminator Active Deterrence mrežna kamera

1/2.8" STARVIS CMOS sa progresivnim skeniranjem. Color: 0.005 Lux@F1.6 Maksimalna rezolucija 2560x1920. Fiksna optika 4mm. Kompresija H.265+/H.264+. DWDR. Warm light/IR LED diode, domet dioda 30metara. Audio ulaz/audio izlaz integriran mikrofoni, sirena i zvučnik (podrška two-way talk - dvosmjernu komunikaciju), slot za microSD karticu do 512GB. Video analitika: Tripwire, intrusion (detekcija ljudi). Napajanje 12VDC/PoE, 12.95W max. Nivo zaštite IP66. Materijal: plastika.

Cijena i dobavlјivost na upit



## IPC-SD22404T-GN-S2 PTZ kamera

VK-808

4MP dome PTZ antivandal mrežna kamera

Senzor: 1/3" CMOS progressive sensor. 4 x optički zoom ( 2.7mm -11mm) + 16 x digitalni, auto/manual fokus. Kompresija: H.265 /H264. Osjetljivost: color 0.05Lux / F1.6 , b/w 0.005Lux. Maskiranje privatnosti: 24 zone. Napajanje: 12VDC/1.5A, PoE. Potrošnja: 10W. Zaštita: IP66, IK10. Podrška putem pametnih telefona. Odgovarajuća baza PFA137, PFB203W, PFA137 + PFA152-E. Materijal: metal.

Cijena i dobavlјivost na upit



## IPC-SD29204UE-GN 2MP PTZ kamera Rasprodaja

VK-1012

2MP IR PTZ mrežna kamera sa starlight tehnologijom

Senzor: 1/2.8 STARVIS™ CMOS senzor. Širina objektiva 2.7-11mm, auto/manual fokus. Kompresija: H.265/H264/MJPEG. Rezolucija 1920x1080. Osjetljivost: color 0.0005Lux / F1.6 , b/w 0.0005Lux . Ima integriran mikrofoni. Napajanje: DC 12V/1.5A, PoE . Potrošnja: 13W. Zidni nosač je PFB302S. Materijal: metal.

Cijena i dobavlјivost na upit



## IPC-SD42212T-HN PTZ kamera Rasprodaja

VK-593

2 MP dome PTZ antivandal kamera

Senzor: 1/2.7 CMOS sa progresivnim skeniranjem. 12 x optički zoom ( 5.1mm-61.2mm) + 16 x digitalni, auto/manual fokus. Kompresija: H.264/H264+. Osjetljivost: color 0.05Lux / F1.6 , b/w 0.005Lux . Audio: 1in/1out. Alarm 2 in/1 out. Napajanje: 24Vac/1.5A, PoE+. Potrošnja: 12W. Zaštita: IP66, IK10. Podrška putem pametnih telefona: iPhone, iPad, Android, Windows Phone. Odgovarajuća baza PFA102 + PFB302S.

Cijena i dobavlјivost na upit



## IPC-SD65220-HN PTZ kamera 20x Rasprodaja

VK-318

2MP mrežna kamera u PTZ kućištu

Senzor: 1/3" CMOS sa progresivnim skeniranjem, 20 x optički zoom ( 4.7mm-94mm) + 16 x digitalni, Kompresija: H.264 / MJPEG . Osvjetljenje: color 0.05Lux/F1.6, b/w 0.005Lux. SD memorijska kartica max 64GB , alarm 7-in/2-out. Napajanje: 24Vac /3A, 15W (40W Heater on). Zaštita: IP67. Dolazi sa DH-69FB ,DH-PFA111, AC24V/3A, opcionalo DH-PFB300C, DH-PFB301C, DH-PFA112, DH-PFA113, DH-PFB301S, DH-PFA120, DH-PFA150, DH-PFA151.

Cijena i dobavlјivost na upit



## IPC-SD49225GB-HNR

VK-1053

2MP IR mrežna PTZ kamera sa starlight tehnologijom

1/2.8" STARVIS CMOS senzor. Color: 0.005 Lux@F1.6 Maksimalna rezolucija 2560x1440. Motorizovani varifokal 5-125 mm. Kompresija H.265+/H.264+. Domet iluminatora 100 metara. audio ulaz/audio izlaz; alarm 1 ulaz, 1 izlaz. Slot za micro SD karticu do 512GB. Video analitika: Tripwire, intrusion (detekcija ljudi). Napajanje 12VDC/PoE, 20W max. Nivo zaštite IP65.

Cijena i dobavlјivost na upit



## IPC-SD4A425DB-HNY PTZ kamera

VK-1018

4MP IR mrežna WizSense PTZ kamera sa starlight tehnologijom

Senzor: 1/2.8 STARVIS™ CMOS .Manuelni varifokal 2.7- 11 mm. Kompresija: H.265+; H.264; H.265; MJPEG. Rezolucija 2560x 1440. Osjetljivost: color 0.005Lux / F1.6. WDR 120 db. IR domet 100m. Zaštita IP66. Slot SD kartice 512GB. Pametne detekcije: tripwire, intrusion, parking detection, missing object, people gathering, face detection. Napajanje: 12VDC/2A, PoE+. Potrošnja: 21.5W max.

Cijena i dobavlјivost na upit



## IPC-SD49425GB-HNR kamera

VK-1043

4MP mrežna kamera u PTZ kućištu sa Starlight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on). Maksimalna rezolucija 2560x1440. Varifokalna optika 5 - 125 mm, 25x optički zum. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP66. 120dB WDR. Domet IC dioda 100 metara. Slot za microSD karticu do 512GB. 1x audio in, 1x audio out. 2x alarm in, 1x alarm out. Video analitika: Object Abandoned/Missing, Tripwire and intrusion, crossing fence detection, loitering detection, abandoned/missing object. Fast moving, parking detection, people gathering. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, SMD 4.0. 12V napajanje, PoE. Dolazi sa zidnim nosačem PFB305W. Odgovarajuća dozna je PFA120. Ugaoni nosač je PFA151. Nosač za banderu je PFA150.

Cijena i dobavlјivost na upit



## IPC-SD5A225XA-HNR-PTZ kamera

VK-862

2MP mrežna kamera u PTZ kućištu sa Starlight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on). Maksimalna rezolucija 1920x1080. Varifokalna optika 5.4 - 135 mm, 25x optički zum. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 150 metara. Slot za microSD karticu do 256GB. 1x audio in, 1x audio out. 2x alarm in, 1x alarm out. Video analitika: Object Abandoned/Missing, Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, SMD Plus, Auto Tracking, Face Detection. 24V napajanje, PoE+. Dolazi sa zidnim nosačem PFB305W i napajanjem. Nosač za baneru je PFA150. Ugaoni nosač je PFA151. Odgovarajuća dozna je PFA120.

Cijena i dobavlјivost na upit



## IPC-SD5A225GB-HNR kamera

VK-1064

2MP mrežna kamera u PTZ kućištu sa Starlight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on). Maksimalna rezolucija 1920x1080. Varifokalna optika 4.8 - 120 mm, 25x optički zum. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 150 metara. Slot za microSD karticu do 512GB. 1x audio in, 1x audio out. 2x alarm in, 1x alarm out. Video analitika: Object Abandoned/Missing, Tripwire and intrusion, Climbing fences, loitering detection, abandoned/missing object, fast moving, parking detection, people gathering. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, SMD 4.0, Auto Tracking, Face Detection. 24V napajanje, PoE+. Dolazi sa zidnim nosačem PFB305W i napajanjem. Odgovarajuća dozna PFA140, PFA120. Nosač za baneru je PFA150. Ugaoni nosač je PFA151. Odgovarajuća dozna je PFA120.

Cijena i dobavlјivost na upit



## IPC-SD6CE225U-HNI kamera

VK-925

2MP starlight IR PTZ mrežna kamera

1/2.8 STARVIS™ CMOS senzor. Rezolucija 1920 x 1080. WDR 120 dB. Kompresija: H.265+/H.265, H.264+/H.264. Osjetljivost: color: 0.005Lux@F1.6; B/W: 0.0005Lux @F1.6; 0Lux (IR on). Pametne detekcije: tripwire, intrusion, face detection, heat map. IR domet: 200m. Napajanje: DC24V/2.5A, PoE+. Potrošnja: max. 25W IR uklj.. Zaštita: IP67, IK10. Dolazi sa PFB305W i DC24V/2.5A, opciono PFA111, PFA140, PFB300C, PFA120, PFA150, PFA151, PFB303S.

Cijena i dobavlјivost na upit





## IPC-SD49825GB-HNR PTZ kamera

8MP IR mrežna PTZ kamera sa starlight tehnologijom

1/2.8" STARVIS™ CMOS senzor. Rezolucija 3840 x 2160. WDR 120 dB. Kompresija: H.265+; H.264; H.265; MJPEG (Osjetljivost: color: 0.005Lux@F1.6; B/W: 0.0005Lux @F1.6; 0Lux (IR on)). Pametne detekcije: tripwire, intrusion, face detection. IR domet: 100 metara. Napajanje: 12 VDC, 3 A, PoE. Potrošnja: max. 20 W IR uklj. Zaštita: IP66. Dolazi sa PFB305W i DC12V/3 A, opciono PFA111, PFB301C, PFB300C, PFA120, PFA150, PFA151, PFB303S.

VK-1091-D

Cijena i dobavljaljivost na upit



## IPC-SD50430U-HNI kamera Rasprodaja

4MP PTZ mrežna kamera

1/3 CMOS senzor. Rezolucija 2592 x 1520. WDR 120 dB. Kompresija: H.265+; H.265; H.264+; H264. (Osjetljivost: color: 0.05Lux@F1.6; B/W: 0.005Lux @F1.6). Pametne detekcije: tripwire, intrusion, face detection, missing object, heat map. Napajanje: C24V/1.5A. Potrošnja: max. 23 W. Zaštita: IP67, IK10. Audio 1 in, 1 out; alarm 2 in, 1 out. Materijal: metal.

VK-631

Cijena i dobavljaljivost na upit



## IPC-SD60430U-HNI kamera Rasprodaja

4MP PTZ antivandal mrežna kamera

1/3" CMOS senzor. Rezolucija: 2592 x 1520. WDR 120db. Kompresija: H.265+/H265, H264H+/H264. Osjetljivost: color: 0.05Lux, b/w :0.005Lux. Pametne detekcije: virtuelna linija, uljez, nestali/napušteni objekat, detekcija lica, podržava auto trekning, 300 preset pozicija. Alarm : 7 ul/1 izl. Audio: 1 ul/1 izl. Napajanje: 24Vac/1.5A, PoE+. Potrošnja: 13W /20W. Zaštita: IK10, IP67. Dolazi sa PFB303W, PFA111, AC24V/3A, opciono PFA140, PFB300C, PFA120, PFA150, PFA151, PFB303S.

VK-750

Cijena i dobavljaljivost na upit



## IPC-SD5A432GB-HNR PTZ kamera

4MP IR mrežna WizSense PTZ kamera sa starlight tehnologijom

1/2.8" STARVIS™ CMOS senzor. Color: 0.005 Lux@F1.6. Maksimalna rezolucija 2560x1440. Motorizovani varifokal 4.8-154 mm. Kompresija: H.265+/H.264+. Domet iluminatora 150 metara. audio ulaz/audio izlaz; larm 2ulaz/1 izlaz. Slot za microSD karticu do 512 GB. Video analitika: Tripwire, intrusion (detekcija ljudi), uključen auto tracking. Napajanje 24VDC/PoE, 22W max. Nivo zaštite IP67. Dolazi uz PFB305W, DC24V/2.5A, PFA111, PFA140, PFB300C, PFB301C, PFA120, PFA150, PFA151.

VK-1033

Cijena i dobavljaljivost na upit



## IPC-SD5A432XB-HNR 4MP pokretna kamera

4MP mrežna kamera u PTZ kućištu sa Starlight tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on). Maksimalna rezolucija 2560x1440. Varifokalna optika 4.8 - 154 mm, 32x optički zum. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 150 metara. Slot za microSD karticu do 512GB. 1x audio in, 1x audio out. 2x alarm in, 1x alarm out. Video analitika: Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, SMD Plus, Auto Tracking, Face Detection. 24V napajanje, PoE+. Dolazi sa zidnim nosačem PFB305W i napajanjem. Odgovarajuća dozna je PFA120. Nosač za banderu je PFA150. Ugaoni nosač je PFA151.

VK-855-1

Cijena i dobavljaljivost na upit



## IPC-SD6CE445XA-HNR 4 Mp PTZ kamera

4 MP WizSense Starlight PTZ antivandal kamera

1/2.8 STARVIS™ CMOS senzor. Rezolucija 2560 x 1440. WDR 120 dB. Kompresija: H.265+/H265, H264H+/H264. Osjetljivost: color: 0.005Lux@F1.6; B/W: 0.0005Lux @F1.6; 0Lux (IR on). Pametne detekcije: virtuelna linija, uljez, nestali/napušteni objekat, detekcija lica, klasifikacija ljudi/motorna vozila/ostala vozila vozila podržava auto trekning. Alarm : 7 ul/2 izl. Audio: 1 ul/1 izl. IR domet: 250m. Napajanje: 24Vac/3A, PoE+. Potrošnja: max. 26W IR uklj. Zaštita: IP67, IK10. Dolazi sa PFB305W i AC24V/3A, opciono PFA111, PFA140, PFB300C, PFA120, PFA150, PFA151, PFB303S.

VK-846

Cijena i dobavljaljivost na upit





## TPC-SD2241-TB7F8-S2 termalna kamera

VK-933-1

4 MP mrežna termalna hibridna kamera u dome kućištu

Rezolucija 1280 x 960. DWDR. Kompresija: H.265; H.264; H.264H. Osjetljivost: color: 0.05Lux. Pametne detekcije: heat detection, cold/hot spot trace, tripwire, intrusion, smoking detection, call detection. Alarm 2 in, 1 out; audio 1 in, 1 out. Napajanje 12VDC, PoE+. Zidni nosač je PFB305W.

Cijena i dobavlјivost na upit



## IPC-SD6CE445GB-HNR PTZ kamera

VK-1090

4MP IR mrežna PTZ kamera sa starlight tehnologijom

1/2.8 STARVIS™ CMOS senzor. Rezolucija 2560 x 1440. WDR 120 dB. Kompresija: H.265+/H265, H264/H265. Osjetljivost: color: 0.005Lux@F1.6; B/W: 0.0005Lux @F1.6; 0Lux (IR on). Pametne detekcije: tripwire, intrusion, climbing fences, loitering detection; abandoned object; fast moving. IR domet: 250m. Napajanje: 24 VDC, 2.5 A, PoE+. Potrošnja: max. 25W IR. Zaštita: IP67, IK10. Dolazi sa PFB305W i DC24V/2.5A, opciono PFA111, PFB300C, PFA120, PFA150, PFA151, PFB303S, PFB301S-E, PFB301C.

Cijena i dobavlјivost na upit



## IPC-SD5A825GA-HNR 8 MP- PTZ CAMERA

VK-946-1

8MP IR WizSense mrežna PTZ kamera sa starlight tehnologijom

1/1.8 CMOS senzor. Rezolucija 3840 x 2160. WDR 120 dB. Kompresija: H.265; H.264B; H.264; H.264H; MJPEG. Osjetljivost: color: 0.005Lux@F1.6; B/W: 0.0005Lux @F1.6; 0Lux (IR on). Pametne detekcije: tripwire, intrusion, face detection, auto tracking. IR domet: 150m. Napajanje: 24 VDC, 2.5 A, PoE+. Potrošnja: max. 21W IR uklj. Zaštita: IP67. Dolazi sa PFB305W i DC24V/2.5 A, opciono PFA111, PFA140, PFB300C, PFA120, PFA150, PFA151, PFB303S.

Cijena i dobavlјivost na upit



## IPC-SD2A500NB-GNY-A-PV

VK-1052-1

5MP mrežna kamera u PT kućištu sa Dual Illuminator tehnologijom.

1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.05Lux@F1.6; B/W: 0.005Lux@F1.6; 0Lux@F1.6 (iluminator on). Maksimalna rezolucija 2560x1900. Fiksna optika 4mm. Kompresija H.265/H.264. Nivo zaštite IP66. DWDR. Domet IR/LED dioda 30 metara. Slot za microSD karticu do 256GB. Integriran mikrofoni i zvučnik. Zvučna i svjetlosna signalizacija. Video analitika: SMD 3.0, tripwire, intrusion detection, covjek/vozilo. Napajanje 12VDC, 1.5A.

Cijena i dobavlјivost na upit



## SDT4E425-8P-GB-APV1

VK-1148

8+4MP TiOC Dual light panoramska mrežna PTZ kamera

Cijena i dobavlјivost na upit



## IPC-SD6C230T-HN IP kamera 2mp 30zoom

VK-517

2MP IR mrežna PTZ kamera sa 30x optičkim zumom

Cijena i dobavlјivost na upit



**dahua**  
TECHNOLOGY



NOVO

## SD3E410DB-GNY-A-PV1

VK-1162

4MP mrežna TiOC kamera u PTZ kućištu sa Dual Illuminator tehnologijom

1/2.8" CMOS sa progresivnim skeniranjem. Color:0.005Lux@F1.6;B/W: 0.005Lux@F1.6; 0Lux@F1.6 (iluminator on). Maksimalna rezolucija 2560x1440. Motorizovana optika 4 mm-40 mm. Kompresija H.265/H.264. WDR120dB. Domet IR/LED dioda 70/30 metara. Slot za microSD karticu do 512GB. Integrisan mikrofoni i zvučnik. Zvučna i svetlosna signalizacija. Video analitika:SMD 3.0, tripwire,intrusion detection, covjek/vozilo,detekcija llica. Nivo zaštite IP66.Napajanje 12VDC,2A ili PoE+.

Cijena i dobavljaljivost  
na upit



## NVR104-P snimač sa 4PoE Rasprodaja

Mrežni video snimač za 4 (4PoE) kanala.

Maksimalna rezolucija snimanja 2MP. Bandwidth In 56Mbps, Bandwidth Out 56Mbps. Kompresija snimanja, H.264. 1 x HDMI izlaz, 1 x VGA izlaz  
1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 1TB(2.5).

VR-295

Cijena i dobavljaljivost na upit



## NVR1104HS-W-S2-CE snimač

4CH WI-FI snimač

Smart H.265/Smart H.264. Mrežni bandwidth: 40Mbps žičani 16Mbps bežični. WI FI : IEEE 802.11b/g/n domet do 100m na otvorenom prostoru. Dualna antena 2x2 MIMO .VGA/HDMI x1 .Rezolucija 6 MP; 5 MP; 4 MP; 3 MP; 2 MP. Max Decoding: 1ch 6 MP/ 2ch 4 MP/ 4ch 1080p@.Kompresija H.265+/H.265/H.264+/H.264 . Audio kompresija G.711A/G.711U/PCM/G726. HDD 1 SATA max 8TB/. Radna temperatura -10°C + 45 °C. Napajanje 12V/1.5 A

VR-479

Cijena i dobavljaljivost na upit



## NVR4232 32ch NVR snimač Rasprodaja

Mrežni video snimač za 32 kanala

VR-254

Cijena i dobavljaljivost na upit



## NVR1108HS-W-S2 snimač

8CH WI-FI snimač

Smart H.265/Smart H.264. Mrežni bandwidth: 40Mbps žičani 16Mbps bežični. WI FI : IEEE 802.11b/g/n domet do 100m na otvorenom prostoru. Dualna antena 2x2 MIMO .VGA/HDMI x1 .Rezolucija 6 MP; 5 MP; 4 MP; 3 MP; 2 MP. Max Decoding: 1ch 6 MP/ 2ch 4 MP/ 4ch 1080p@.Kompresija H.265+/H.265/H.264+/H.264 . Audio kompresija G.711A/G.711U/PCM/G726. HDD 1 SATA max 8TB/. Radna temperatura -10°C + 45 °C. Napajanje 12V/1.5 A

VR-472

Cijena i dobavljaljivost na upit



## NVR4104HS-4KS2/L 4 kanalni snimač

Mrežni video snimač za 4 kanala.

Maksimalna rezolucija snimanja 8MP. Bandwidth In 80Mbps, Bandwidth Out 60Mbps. Kompresija snimanja, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 10TB. Face Detection, Perimeter Protection, SMD Plus, People counting by camera.

VR-451-1

Cijena i dobavljaljivost na upit



## NVR4108HS-4KS3 snimač

Mrežni video snimač sa 8 kanala.

Maksimalna rezolucija snimanja 12MP. Bandwidth In 80Mbps, Bandwidth Out 60Mbps. Kompresija snimanja H.265+, H.264+ Smart. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. AI preko kamere(FD,FR,brojanje ljudi,SMD plus);4CH SMD plus(snimač)

VR-382-3

Cijena i dobavljaljivost na upit



## NVR4104HS-EI snimač

VR-480

Mrežni video snimač sa 4 kanala i AI tehnologijom

Maksimalna rezolucija snimanja 16MP. Bandwidth dolazni 80Mbps, Bandwidth odlazni 80Mbps. Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0 Mogućnost priključenja 1HDD maksimalnog kapaciteta 16TB. Detekcija lica, prepoznavanje lica ,zaštita perimetra i SMD Plus.

Cijena i dobavlјivost na upit



## NVR4108HS-EI snimač

VR-482

Mrežni video snimač sa 8 kanala i AI tehnologijom

Maksimalna rezolucija snimanja 16MP. Bandwidth dolazni 80Mbps, Bandwidth odlazni 80Mbps. Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0 Mogućnost priključenja 1HDD maksimalnog kapaciteta 16TB. Detekcija lica, prepoznavanje lica ,zaštita perimetra i SMD Plus.

Cijena i dobavlјivost na upit



## NVR4216-4KS3

VR-346-3

Mrežni video snimač za 16 kanala.

Maksimalna rezolucija snimanja 12MP. Bandwidth In 160Mbps, Bandwidth Out 80Mbps. Kompresija snimanja H.265+, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2x alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 20TB po disku. Face Detection, Perimeter Protection, SMD Plus, People counting by camera. SMD Plus by recorder

Cijena i dobavlјivost na upit



## NVR2108HS-8P-S3 snimač

VR-394-2

Mrežni video snimač sa 8 (PoE) kanala

Maksimalna rezolucija snimanja 12MP. Bandwidth dolazni 80Mbps, Bandwidth odlazni 60Mbps. Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 4 x PoE 10/100Mbps, total PoE 36W max na 1 port 25w. 2x USB 2.0 Mogućnost priključenja 1HDD maksimalnog kapaciteta 16TB. Perimeter Protection( 4 kanala sa kamere), SMD Plus (4 kanala sa kamere).

Cijena i dobavlјivost na upit



## NVR4232-4KS3 snimač

VR-345-3

Mrežni video snimač za 32 kanala

Maksimalna rezolucija snimanja 12MP. Bandwidth In 160Mbps, Bandwidth Out 128Mbps. Kompresija snimanja H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2x alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 20TB po disku. Face Detection, Perimeter Protection, SMD, People counting by camera.

Cijena i dobavlјivost na upit



## NVR4832-16P-4KS2 snimač Rasprodaja

VR-388

Mrežni video snimač za 32 (16PoE) kanala

Maksimalna rezolucija snimanja 8MP. Bandwidth In 200Mbps, Bandwidth Out 96Mbps. Kompresija snimanja H.265+, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 16x alarm in, 4x alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 8HDD maksimalnog kapaciteta 10TB po disku. Face Detection, Perimeter Protection, SMD, People counting by camera.

Cijena i dobavlјivost na upit





## NVR4116-4KS2 snimač

VR-377-1

Mrežni video snimač za 16 kanala

Maksimalna rezolucija snimanja 8MP. Bandwidth In 200Mbps, Bandwidth Out 96Mbps. Kompresija snimanja H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 16x alarm in, 4x alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 4HDD maksimalnog kapaciteta 10TB po disku. Face Detection, Perimeter Protection, SMD, People counting by camera.

Cijena i dobavlјivost na upit



## NVR2104HS-P-S3 snimač

VR-473-1

Mrežni video snimač za 4 kanala, sa 4-kanalnim PoE

Maksimalna rezolucija snimanja 12MP. Bandwidth dolazni 80Mbps, Bandwidth odlazni 60Mbps. Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 4 x PoE 10/100Mbps, total PoE 36W max na 1 port 25w. 2x USB 2.0 Mogućnost priključenja 1HDD maksimalnog kapaciteta 16TB. Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## NVR4116HS-4KS3

VR-396-3

Mrežni video snimač sa 16 kanala

Maksimalna rezolucija snimanja 12MP. Bandwidth In 160Mbps, Bandwidth Out 80Mbps. Kompresija snimanja H.265+, H.264+ Smart. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. AI preko kamere (FD, FR, brojanje ljudi, SMD plus) ; 4CH SMD plus (snimač)

Cijena i dobavlјivost na upit



## NVR2104HS-4KS3

VR-392-6

Mrežni video snimač sa 4 kanala

Maksimalna rezolucija snimanja 12MP. Bandwidth In 80Mbps, Bandwidth Out 60Mbps. Kompresija snimanja, H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## NVR2108HS-4KS3

VR-405-6

Mrežni video snimač sa 8 kanala

Maksimalna rezolucija snimanja 12MP. Bandwidth In 80Mbps, Bandwidth Out 60Mbps. Kompresija snimanja, H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit



## NVR2108HS-8P-4KS3

VR-394-3

Mrežni video snimač za 8 kanala, sa 8-kanalnim PoE

Maksimalna rezolucija snimanja 12MP. Bandwidth dolazni 144Mbps, Bandwidth odlazni 72Mbps. Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 8 x PoE 10/100Mbps, total PoE 72W max na 1 port 25w. 2x USB 2.0 Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. Perimeter Protection, SMD Plus.

Cijena i dobavlјivost na upit





## NVR4108HS-8P-4KS3

Mrežni PoE video snimač sa 8 kanala.

Maksimalna rezolucija snimanja 12MP. Bandwidth In 80Mbps, Bandwidth Out 60Mbps. Kompresija snimanja H.265+, H.264+ Smart. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 20TB. 8 PoE portova. AI preko kamere (FD, FR, brojanje ljudi, SMD plus); 4CH SMD plus (snimač)

VR-511

Cijena i dobavljalivost na upit



## NVR4208-8P-I snimač Rasprodaja

Mrežni video snimač sa 8 (PoE) kanala i AI tehnologijom

Maksimalna rezolucija snimanja 12MP. Bandwidth dolazni 80Mbps (AI uključen), Bandwidth odlazni 80Mbps (AI uključen). integrisan PoE (8 kanala) Kompresija snimanja, Smart H.265, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10/100/1000Mbps mrežni interfejs. 2x USB 2.0 Mogućnost priključenja 2HDD maksimalnog kapaciteta 10TB. Detekcija lica, prepoznavanje lica, zaštita perimetra i SMD Plus.

VR-279-1

Cijena i dobavljalivost na upit



NOVO

## NVR4216-16P-4KS3

Mrežni PoE video snimač za 16 kanala.

Maksimalna rezolucija snimanja 12MP. Bandwidth In 160Mbps, Bandwidth Out 80Mbps. Kompresija snimanja H.265+, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2x alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 20TB po disku. 16 PoE ulaza. Face Detection, Perimeter Protection, SMD Plus, People counting by camera. SMD Plus by recorder

VR-376-3

Cijena i dobavljalivost na upit



## NVR5232 32ch SNIMAC Rasprodaja

Mrežni video snimač za 32 kanala

VR-201

Cijena i dobavlјivost  
na upit



## DH-NVR7816-DR 16ch NVR

VR-242-1

Cijena i dobavlјivost  
na upit



## NVR5216-EI snimač

Mrežni video snimač sa 16 kanala i AI tehnologijom.

VR-491

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 16TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost  
na upit



## NVR5232-EI snimac

Mrežni video snimač sa 32 kanala i AI tehnologijom.

VR-492

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 16TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost  
na upit



## NVR5216-16P-EI snimač

Mrežni video snimač sa 16 (PoE) kanala i AI tehnologijom.

VR-483

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 20TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost  
na upit



## NVR5432-EI

Mrežni video snimač sa 32 kanala i AI tehnologijom.

VR-484

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 2 x HDMI izlaz, 2 x VGA izlaz. 16x alarm in, 6 alarm out. 1x audio in, 2x audio out. 2x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. Mogućnost priključenja 4HDD maksimalnog kapaciteta 16TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost  
na upit





## NVR5464-EI snimač

VR-488

Mrežni video snimač sa 64 kanala i AI tehnologijom.

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 2 x HDMI izlaz, 2 x VGA izlaz. 16x alarm in, 6 alarm out. 1x audio in, 2x audio out. 2x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. Mogućnost priključenja 4HDD maksimalnog kapaciteta 16TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost na upit



## NVR5216-8P-I snimač Rasprodaja

VR-453-1

Mrežni video snimač sa 16 (8PoE) kanala i AI tehnologijom.

Maksimalna rezolucija snimanja 32MP. Bandwidth In 320Mbps, Bandwidth Out 320Mbps. Kompresija snimanja Smart H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 8TB po disku. Perimeter protection, face detection, face recognition, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost na upit



## NVR5864-EI snimač

VR-353-1

Mrežni video snimač sa 64 kanala i AI tehnologijom.

Maksimalna rezolucija snimanja 32MP. Bandwidth In 384Mbps, Bandwidth Out 384Mbps. Kompresija snimanja Smart H.265+. 2 x HDMI izlaz, 2 x VGA izlaz. 16x alarm in, 6 alarm out. 1x audio in, 2x audio out. 2x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. Mogućnost priključenja 8HDD maksimalnog kapaciteta 20TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost na upit



## NVR5216-16P-I snimač Rasprodaja

VR-453

Mrežni video snimač sa 16 (PoE) kanala i AI tehnologijom.

Maksimalna rezolucija snimanja 32MP. Bandwidth In 320Mbps, Bandwidth Out 320Mbps. Kompresija snimanja Smart H.265+. 1 x HDMI izlaz, 1 x VGA izlaz. 4x alarm in, 2 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. Mogućnost priključenja 2HDD maksimalnog kapaciteta 8TB po disku. Perimeter protection, face detection, face recognition, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost na upit



## NVR5432-16P-I/L snimač

VR-455-1

Mrežni video snimač sa 32 (16PoE) kanala i AI tehnologijom.

Maksimalna rezolucija snimanja 24MP. Bandwidth In 320Mbps, Bandwidth Out 320Mbps. Kompresija snimanja Smart H.265+. 2 x HDMI izlaz, 1 x VGA izlaz. 16x alarm in, 6 alarm out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. Mogućnost priključenja 4HDD maksimalnog kapaciteta 10TB po disku. Perimeter protection, face detection, face recognition, SMD Plus, video metadata (human, motor-vehicle, non-motor vehicle). ANPR, people counting, stereo analysis, crowd distribution, heat map.

Cijena i dobavlјivost na upit



## NVR608-64-4KS2 snimač

VR-333

Mrežni video snimač sa 64 kanala

Maksimalna rezolucija 3840 x 2160 px, multiskrin (1/4/8/9/16/25/36). OSD za prikaz informacija kao što su naziv kamera, vrijeme, upis, detekcija pokreta, gubitak videa. Kompresija videa H.265/H.264/MJPEG, maks. rezolucija pri upisu 12Mpx, brzina zapisa do 384 Mbps. Brzina pri prikazu varira (128 Mbps u RAID5 modu / 64 Mbps u singl HDD modu). 16 alarmnih ulaza, 8 relejnih izlaza, interfejsi (2 x RJ45, 4 x USB, 1 x RS232, 1 x RS485, 1 x eSATA). RAID podrška (0/1/5/6/10), ONVIF 2.4, CGI, do 128 korisnika. 8 SATA III priključaka za HDD-ove do 8TB. Pametno praćenje i inteligentni video (tripwire, people counting, heat map, otpakivanje fisheye kamera), ANR funkcija. AC100 ~ 240V napajanje, maks. 20 W bez HDD-a. Radna temperatura -10°C do +55°C, vlažnost 0% do 90%. Ugradnja u rek.

Cijena i dobavlјivost na upit







## NVR608H-32-XI kanalni snimač

Mrežni video snimač sa 32 kanala i AI tehnologijom

Maksimalna rezolucija 3840 x 2160 px, podrška za multiskrin. Kompresija videa H.265+/H.264+/MJPEG, maks. rezolucija pri upisu 32Mpx, brzina zapisa do 1280Mbps(AI isključen)640 Mbps(AI uključen). 16 alarmnih ulaza, 8 relejnih izlaza, razni interfejsi (2 x RJ45-2.5Gbps, 4 x USB, 1 x RS232, 1 x RS485, 1 x eSATA). RAID podrška (0/1/5/6/10), ONVIF, CGI, do 128 korisnika. 8 SATA III priključaka za HDD-ove do 16TB. 8ch Prepoznavanje lica;32ch zaštita perimetra;32ch SMD plus. AC100 ~ 240V napajanje, do 18 W bez HDD-a. Radna temperatura -10°C do +55°C, vlažnost 10% do 93%. Ugradnja u rek.

VR-486-1

PROJEKтни MODEL



## NVR608H-128-XI Mrežni snimač 128 kanala

Mrežni video snimač sa 128 kanala -AI tehnologijom

Maksimalna rezolucija 3840 x 2160 px, podrška za multiskrin. Kompresija videa H.265+/H.264+/MJPEG, maks. rezolucija pri upisu 32Mpx, brzina zapisa do 1280Mbps(AI isključen)640 Mbps(AI uključen). 16 alarmnih ulaza, 8 relejnih izlaza, razni interfejsi (2 x RJ45-2.5Gbps, 4 x USB, 1 x RS232, 1 x RS485, 1 x eSATA). RAID podrška (0/1/5/6/10), ONVIF, CGI, do 128 korisnika. 8 SATA III priključaka za HDD-ove do 20TB. 8ch Prepoznavanje lica;32ch zaštita perimetra;32ch SMD plus. AC100 ~ 240V napajanje, do 18 W bez HDD-a. Radna temperatura -10°C do +55°C, vlažnost 10% do 93%. Ugradnja u rek.

VR-509

PROJEKтни MODEL



## NVR608H-64-XI

Mrežni video snimač sa 64 kanala -AI tehnologijom

Maksimalna rezolucija 3840 x 2160 px, podrška za multiskrin. Kompresija videa H.265+/H.264+/MJPEG, maks. rezolucija pri upisu 32Mpx, brzina zapisa do 1280Mbps(AI isključen)640 Mbps(AI uključen). 16 alarmnih ulaza, 8 relejnih izlaza, razni interfejsi (2 x RJ45-2.5Gbps, 4 x USB, 1 x RS232, 1 x RS485, 1 x eSATA). RAID podrška (0/1/5/6/10), ONVIF, CGI, do 128 korisnika. 8 SATA III priključaka za HDD-ove do 20B. 8ch Prepoznavanje lica;32ch zaštita perimetra;32ch SMD plus. AC100 ~ 240V napajanje, do 18 W bez HDD-a. Radna temperatura -10°C do +55°C, vlažnost 10% do 93%. Ugradnja u rek.

VR-510

PROJEKтни MODEL



## NVR7816-DR 16ch IP snimač Rasprodaja

Mrežni video snimač sa 8 HDD i 16 kanala

VR-242

Cijena i dobavlјivost na upit





## PFS3005-5GT-L-V2 switch

VO-432-3

PFS3005-5GT-L-V2

5- portni switch · Brzina forvardovanja paketa: 7.44Mpps · Temp. opseg: -10°C ~ 55°C · Dimenzije:125 mm × 65 mm × 22 m Ethernet portovi: 5 × 10/100/1000 ethernet portovi(switch)

Cijena i dobavlјivost na upit



## PFS3005-5GT-V2 switch

VO-432-2

PFS3005-5GT-V2 switch

5- portni switch · Brzina forvardovanja paketa: 7.44Mpps · Temp. opseg: -10°C ~ 55°C · Dimenzije:150 mm × 110 mm × 42 mm Ethernet portovi: 5 × 10/100/1000 ethernet portovi(switch)

Cijena i dobavlјivost na upit



## PFS3008-8GT-L-V2 switch

VO-433-3

PFS3008-8GT-L-V2

8- porttni switch · Brzina forvardovanja paketa11.9mbps · Temp. opseg: -10°C ~ 55°C · Dimenzije:125 mm × 65 mm × 22 m Ethernet portovi: 5 × 10/100/1000 ethernet portovi(switch)

Cijena i dobavlјivost na upit



## PFS3008-8GT-V2 switch

VO-433-2

PFS3008-8GT-V2

8- porttni switch · Brzina forvardovanja paketa11.9mbps · Temp. opseg: -10°C ~ 55°C · Dimenzije:133.5 mm × 56.0 mm × 22.0 mm Ethernet portovi: 5 × 10/100/1000 ethernet portovi(switch)

Cijena i dobavlјivost na upit



## TAM1GT1GT-30 PoE injektor 30W

VO-266

TAM1GT1GT-30 PoE injektor 30W

PoE injektor 30W, 1\*10/100/1000 Base-T 1\*10/100/1000 Base-T( PoE power supply), Supports IEEE802.3af, IEEE802.3at standard, radna temperatura -10°C~55°C

Cijena i dobavlјivost na upit



## GSFP-850-MMF SFP modul

VO-283

Gigabitni optički modul.

Multimodni LC konektor, maksimalna udaljenost prenosa 550m, Maksimalna brzina prenosa podataka od 1 Gbps, širok opseg radnih temperatura: -40 ° C do 85 ° C, talasna dužina: sending: 850 nm receive: 850 nm

Cijena i dobavlјivost na upit





## PFT3950 SFP modul multimodni

VO-269

Industrijski SFP modul, 1.25Gbps, Multi-mode 850nm, Double fiber, 500m, LC konektori

Višemodni LC konektor, maksimalna udaljenost prenosa 500m, Maksimalna brzina prenosa podataka od 1,25 Gbps, širok opseg radnih temperatura: -40 ° C do 85 ° C, talasna dužina: transmit: 850 nm receive: 850 nm

Cijena i dobavlјivost na upit



## GSFP-1310R-20-SMF modul single mode

VO-260-1

Gigabitni optički modul.

Jednomodni LC konektor, maksimalna udaljenost prenosa 20km, Maksimalna brzina prenosa podataka od 1 Gbps, širok opseg radnih temperatura: -40 ° C do 85 ° C, talasna dužina: transmit: 1550 nm receive: 1310 nm

Cijena i dobavlјivost na upit



## GSFP-1310T-20-SMF modul single mode

VO-260-2

Gigabitni optički modul.

Jednomodni LC konektor, maksimalna udaljenost prenosa 20km, Maksimalna brzina prenosa podataka od 1 Gbps, širok opseg radnih temperatura: -40 ° C do 85 ° C, talasna dužina: transmit: 1550 nm receive: 1310 nm

Cijena i dobavlјivost na upit



## PFS3006-4ET-60-V2 switch

VO-253-1

4-portni (4+2) neupravlјivi megabitni PoE layer 2 svič.

1 megabitni Hi-PoE port, 3 megabitna PoE porta, 2 megabitna Ethernet porta. PoE power budget 60W, 60W na prvom portu, od 2 do 4 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Metalno kućište. Operativna radna temperatura -10 ~ 55C. Napajanje 53 VDC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## PFS3006-4GT-60-V2 switch

VO-253

4-portni (4+2) neupravlјivi gigabitni PoE svič.

1 gigabitni Hi-PoE port, 3 gigabitna PoE porta, 2 gigabitna Ethernet porta. PoE power budget 60W, 60W na prvom portu, od 2 do 4 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Metalno kućište. Operativna radna temperatura -10 ~ 55C. Napajanje 48 to 57 VDC. Zaštita od prenapona 4KV za PoE portove.

Cijena i dobavlјivost na upit



## PFS3106-4ET-60 switch

VO-397-1

4-portni (4+2) neupravlјivi megabitni PoE layer 2 svič.

1 megabitni Hi-PoE port, 3 megabitna PoE porta, 1 gigabitni Ethernet port, 1 gigabitni SFP port. PoE power budget 60W, 60W na prvom portu, od 2 do 4 porta 30W po portu. Metalno kućište. Operativna radna temperatura -30 ~ 65C. Napajanje 48 to 57V. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit





## PFS3010-8ET-96-V2 10 portni switch sa 8POE

8-portni (8+2) neupravljivi megabitni PoE svič.

1 megabitni Hi-PoE port, 7 megabitna PoE porta, 2 gigabitna Ethernet porta. PoE power budget 96W, 90W na prvom portu, od 2 do 8 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Operativna radna temperatura -10 ~ 55C. Napajanje 48 to 57 VDC. Zaštita od prenapona 6KV za PoE portove.

VO-252

Cijena i dobavlјivost na upit



## PFS3206-4P-96 switch

4-portni (4+2) megabitni PoE layer 2 svič.

4 megabitna PoE porta, 2 gigabitna combs Ethernet/SFP porta. PoE power budget 96W, 30W na prvom, drugom i trecem portu, 60W cetvrti port. Operativna radna temperatura -30 ~ 65C. Napajanje DC48-57V. Zaštita od prenapona 4KV za PoE portove.

VO-422

Cijena i dobavlјivost na upit



## PFS3009-8ETIGT-96 switch

8-portni (8+1) neupravljivi megabitni PoE layer 2 svič.

1 megabitni Hi-PoE port, 7 megabitna PoE porta, 1 gigabitni Ethernet port. PoE power budget 96W, 60W na prvom portu, od 2 do 8 porta 30W po portu. Operativna radna temperatura -10 ~ 55C. Napajanje 53 VDC. Zaštita od prenapona 6KV za PoE portove.

VO-267

Cijena i dobavlјivost na upit



## PFL2106-4ET-96 ePoE switch

PFL2106-4ET-96 ePoE switch

VO-415

Cijena i dobavlјivost na upit



## PFS3110-8ET-96-V2 switch

8-portni (8+2) neupravljivi megabitni PoE layer 2 svič.

2 megabitna Hi-PoE porta, 6 megabitna PoE porta, 1 gigabitni Ethernet porta, 1 gigabitni SFP port. PoE power budget 96W, 60W na prvom i drugom portu, od 3 do 8 porta 30W po portu. Operativna radna temperatura -30 ~ 65C. Napajanje 48 to 57 VDC. Zaštita od prenapona 6KV za PoE portove.

VO-392-1

Cijena i dobavlјivost na upit



## PFS3409-4GT gigabit switch

PFS3409-4GT neupravljivi industrijski switch

9-portni neupravljivi gigabitni svič. 4 gigabitna porta i 1 gigabitni Ethernet port, 4 gigabitna SFP porta. Metalno kućište. Operativna radna temperatura -30 ~ 65C. Napajanje 9 do 57V. Zaštita od prenapona 4KV.

VO-248

Cijena i dobavlјivost na upit



## PFS3010-8GT-96-V2 8-portni switch

VO-431

8-portni (8+2) neupravljivi gigabitni PoE svič.

1 gigabitni Hi-PoE port, 7 gigabitna PoE porta, 2 gigabitna Ethernet porta. PoE power budget 96W, 90W na prvom portu, od 2 do 8 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Operativna radna temperatura -10 ~ 55C. Napajanje 48 to 57 VDC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## LR2110-8ET-120 switch

VO-414

8-portni (8+2) neupravljivi megabitni ePoE layer 2 svič.

2 megabitna Hi-PoE porta, 6 megabitna PoE porta, 1 gigabitni Ethernet porta, 1 gigabitni SFP port. PoE power budget 120W, 60W na prvom i petom portu, 2,3,4,6,7 port po 30W. Operativna radna temperatura -30 ~ 65C. Napajanje 48 to 57 VDC. Zaštita od prenapona 4KV za PoE portove.

Cijena i dobavlјivost na upit



## PFS3211-8GT-120 poe switch

VO-262

PFS3211-8GT-120 poe switch

8-portni switch sa vanjskim napajanjem Kapacitet preklapanja: 33 Gbps · Brzina forvardovanja paketa: 16.37 Mpps · Temp. opseg: -30°C ~ 65°C · Dimenzije: 150 mm × 110 mm × 42 mm · Standardi: IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE · PoE snaga: Port1&5 ≤60W, Port2~4&Port6~8≤30W · ukupno ≤ 120 W · Ethernet portovi: 2\*1000Mbps Base-X 1\*10/100/1000Mbps Base-T 8\*10/100/1000 Base-T (PoE)

Cijena i dobavlјivost na upit



## PFS4218-16ET-240-V3 18 portni switch sa 16POE

VO-221

16-portni (16+2) upravljivi megabitni PoE layer 2 svič.

2 megabitna Hi-PoE porta, 14 megabitna PoE porta, 2 gigabitna combos Ethernet/SFP porta. PoE power budget 240W, 90W na prvom i drugom portu, od 3 do 16 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Svič ima inteligentno upravljanje potrošnjom PoE portova kako bi podaci i napajanje tekli tečno, čak i kad svič ima problem sa napajanjem. Inteligentni PoE prati potrošnju priključenih uređaja a u slučaju velike snaga isključuje jedan po jedan port a ne sve od jednom. Operativna radna temperatura -10 ~ 55C. Napajanje 100 to 240 VAC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## PFS3228-24GT-360 POE switch

VO-270

24-portni (24+2) neupravljivi gigabitni PoE layer 2 svič.

2 gigabitna Hi-PoE porta, 22 gigabitna PoE porta, 2 gigabitna Ethernet porta, 2 gigabitna SFP porta. PoE power budget 360W, 90W na prvom i drugom portu, od 3 do 24 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Svič ima inteligentno upravljanje potrošnjom PoE portova kako bi podaci i napajanje tekli tečno, čak i kad svič ima problem sa napajanjem. Inteligentni PoE prati potrošnju priključenih uređaja a u slučaju velike snaga isključuje jedan po jedan port a ne sve od jednom. Operativna radna temperatura -10 ~ 55C. Napajanje 100 to 240 VAC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## PFS4226-24ET-360 24-V3 -port poe switch

VO-230

24-portni (24+2) upravljivi megabitni PoE layer 2 svič.

2 megabitna Hi-PoE porta, 22 megabitna PoE porta, 2 gigabitna combos Ethernet/SFP porta. PoE power budget 360W, 90W na prvom i drugom portu, od 3 do 24 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Svič ima inteligentno upravljanje potrošnjom PoE portova kako bi podaci i napajanje tekli tečno, čak i kad svič ima problem sa napajanjem. Inteligentni PoE prati potrošnju priključenih uređaja a u slučaju velike snaga isključuje jedan po jedan port a ne sve od jednom. Operativna radna temperatura -10 ~ 55C. Napajanje 100 to 240 VAC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit





## SG5028X switch

VO-450

upravljivi switch sa 24 porta + 4 Uplink

10G SFP+.  
Podržava agregaciju portova i VLAN-ova.  
Podržava STP, RSTP, MSTP i ERPS.  
Podržava web upravljanje, SNMP V1/V2C/V3.  
24 RJ45 10/100/1000Mbps Base-T porta.  
4 SFP+ 10Gbps Base-X porta.  
1 konzolni port.  
Radna temperatura: -20°C ~ +55°C.  
Dimenzije i težina: 528x412x112mm / 4.00Kg.

PROJEKTI MODEL



## CS4010-8GT-110

VO-452

10-portni (8+2 uplink) neupravljivi gigabitni PoE svič.

1 gigabitni Hi-PoE port, 7 gigabitna PoE porta, 2 gigabitna Ethernet porta. PoE power budget 110W, 90W na prvom portu, od 2 do 8 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Operativna radna temperatura -10 ~ 55C. Napajanje 48 to 57 VDC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## HS4412-8ET-120 switch

VO-453

12-portni (8PoE+4SFP) upravljivi switch

Ethernet port brzina : 10 Mbps/100 Mbps . Optička brzina portova . 1000Mbps. 250m dugačka distanca PoE prenosa ( 10Mbps). Poe watchdog. Napajanje 48V-57V DC. Preklopni kapacitet 9.6Gbps. Brzina prosleđivanja paketa : 7.14 Mpps. Snaga po portovima : Port 1-2 ≤ 90 W. port 3-8 ≤ 30W. Ukupno ≤120W .Operativna temperatura -40 °C to +75°C. Mogućnost montaže na DIN šinu.

Cijena i dobavlјivost na upit



## PFS4410-6GT-DP-V2 poe switch

VO-430-D

PFS4410-6GT-DP-V2 Upravlјivi Poe switch

10-portni industrijski gigabitni switch, sa 6 portova gigabitni PoE upravlјivi. 6 Ethernet portova, 4 optička porta, Ethernet port brzina : 10 Mbps/100 Mbps/1000 Mbps. Optička brzina portova . 1000Mbps. 250m dugačka distanca PoE prenosa ( 10Mbps). Poe watchdog. Napajanje 48V-57V DC. Preklopni kapacitet 28Gbps. Brzina prosleđivanja paketa : 14.88 Mpps. Snaga po portovima : Port 1-2 ≤ 90 W. port 3-6 ≤ 30W. Ukupno ≤120W .Operativna temperatura -40 °C to +75°C. Mogućnost montaže na DIN šinu. Potreban adapter za napajanje switch.

Cijena i dobavlјivost na upit



## CS4220-16GT-240

VO-437-1

20-portni (16+2-RJ45+2SFP) upravlјivi gigabitni PoE layer 2 svič.

2 gigabitna Hi-PoE porta, 14 gigabitnih PoE portova, 4 gigabitna combos Ethernet/SFP porta. PoE power budget 240W, 90W na prvom i drugom portu, od 3 do 16 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Svič ima intenzivno upravlјanje potrošnjom PoE portova kako bi podaci i napajanje tekli tečno, čak i kad svič ima problem sa napajanjem. Inteligentni PoE prati potrošnju priključenih uređaja a u slučaju velike snaga isključuje jedan po jedan port a ne sve od jednom. Operativna radna temperatura -10 ~ 55C. Napajanje 100 to 240 VAC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



## CS4218-16ET-135

VO-455

20-portni (16+2-RJ45+2SFP) upravlјivi megabitni PoE layer 2 svič.

2 megabitna Hi-PoE porta, 14 megabitnih PoE portova, 4 gigabitna combos Ethernet/SFP porta. PoE power budget 135W, 90W na prvom i drugom portu, od 3 do 16 porta 30W po portu. PoE watchdog funkcija za automatsko detektovanje i resetovanje kamera koje su izgubile konekciju. Svič ima inteligentno upravlјanje potrošnjom PoE portova kako bi podaci i napajanje tekli tečno, čak i kad svič ima problem sa napajanjem. Inteligentni PoE prati potrošnju priključenih uređaja a u slučaju velike snaga isključuje jedan po jedan port a ne sve od jednom. Operativna radna temperatura -10 ~ 55C. Napajanje 100 to 240 VAC. Zaštita od prenapona 6KV za PoE portove.

Cijena i dobavlјivost na upit



**dahua**  
TECHNOLOGY



NOVO

## CS4228-24GT-375

Dahua CS4228-24GT-375 28 portni switch sa 24PoE 375W

Dahua CS4228-24GT-375 28 portni switch sa 24PoE 375W

VO-454

Cijena i dobavljaljivost  
na upit

**dahua**  
TECHNOLOGY



NOVO

## CS4226-24ET-240

Dahua CS4226-24ET-240 26 portni switch sa 24PoE

Dahua CS4226-24ET-240 26 portni switch sa 24PoE

VO-264-1

Cijena i dobavljaljivost  
na upit

imou



## IPC-F22P Wi Fi bullet kamera

VK-879-1

2MP WiFi kamera u bullet kućištu

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm. Detekcija pokreta, detekcija ljudi, integrisan mikrofoni. Kompresija H.265+/H.264+. Domet IC dioda 30 metara. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. Dualna antena, ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 0.5A, potrošnja 3.5W max. adapter dolazi uz kameru. Nivo zaštite IP67, radna temperatura -30°C do +60°C. Materijal plastika.

Cijena i dobavlјivost na upit

imou

## IPC-C26EP-V2 Wi Fi LOOC bullet kamera 2MP Rasprodaja

VK-886

2MP WiFi Active Deterrence kamera

1/2.7" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm. Detekcija pokreta, PIR detekcija, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB, i spotlight. Kompresija H.265+/H.264+. Noćna vidljivost do 10 m. Podržava skladištenje na Cloud, MicroSD, slot za karticu do 128GB. Dualna antena, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 5VDC, 2A, adapter dolazi uz kameru. Nivo zaštite IP65, radna temperatura -20°C do +50°C. Materijal plastika.

Cijena i dobavlјivost na upit

imou



## IPC-C22FP-C kamera

VK-993

2MP WiFi kamera

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm. Detekcija pokreta, detekcija ljudi, abnormal sound alarm, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 120dB, i spotlight. Kompresija H.265+/H.264+. 4 moda noćne vidljivosti IR do 20 m. Podržava skladištenje na Cloud, MicroSD, slot za karticu do 256GB. Wi Fi do 50m domet na otvorenom, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 5VDC, 1A, potrošnja 3.5W max. adapter dolazi uz kameru. Nivo zaštite IP65, magnetni nosač, radna temperatura -20°C do +45°C. Materijal plastika.

Cijena i dobavlјivost na upit

imou



## IPC-T22EP Dom kamera

VK-888-1

2MP WiFi kamera u dom kućištu.

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm, 16x digital zoom. Detekcija pokreta, detekcija ljudi, integrisan mikrofoni. Kompresija H.265+/H.264+. Domet IC dioda 30 metara. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. Dualna antena, ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 0.5A, potrošnja 3W max. adapter dolazi uz kameru. Za unutrašnju montažu, radna temperatura -20°C do +50°C. Materijal plastika.

Cijena i dobavlјivost na upit

imou



## IPC-F22FEP bullet kamera

VK-923

2MP Wi Fi Active Deterrence Full Color kamera u bullet kućištu

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm, 16x digital zoom. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB i spotlight. Kompresija H.265+/H.264+. Smart Full Color, noćna vidljivost do 30 m. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. Dualna antena, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 1A, potrošnja 5.32W max. adapter dolazi uz kameru. Nivo zaštite IP67, radna temperatura -30°C do +60°C. Materijal metal i plastika.

Cijena i dobavlјivost na upit

imou



## IPC-T26EP dom kamera Rasprodaja

VK-924

2MP WiFi Active Deterrence Turret kamera u dom kućištu.

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 2.8mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB, i spotlight. Kompresija H.265+/H.264+. Domet IC dioda 30 metara. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. Dualna antena, ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 1A, potrošnja 7W max. adapter dolazi uz kameru. Nivo zaštite IP67, radna temperatura -30°C do +60°C. Materijal metal i plastika.

Cijena i dobavlјivost na upit



imou



## IPC-L26P-Imou 2MP kamera sa reflektorom Rasprodaja

VK-880

2MP Wi Fi kamera sa reflektorom

1/2.7" 2 Megapixel progressive CMOS senzor, WI-FI sa dvije antene, IR dometa do 10m, H.265&H.264, fiksni objektiv 2.8mm, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik i sirena 110dB, 2 reflektora sa tri režima aktivacije (ručno/PIR/od sumraka do zore), Motion Detection, PIR detekcija, Alarm notifikacija. Napajanje 240VAC/40W, radna temperatura -30°C~+50°C, IP65. Podržava skladištenje na Cloud, MicroSD, slot za karticu do 256GB.

Cijena i dobavljalivost na upit

imou



## IPC-S22FP pokretna kamera Rasprodaja

VK-892

2MP Wi Fi Active Deterrence Full Color pokretna P&T kamera

1/2.8" 2MP CMOS sa progresivnim skeniranjem. Rezolucija 1920x1080. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB i spotlight. Kompresija H.265/H.264. Dual Antena 120m domet na otvorenom. Smart Tracking, 16x digital zoom, 0~355° Pan & 0~90° Tilt. Smart Full Color, noćna vidljivost do 30 m. Podržava skladištenje na NVR, Cloud, MicroSD, slot za karticu do 256GB. ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 1A, potrošnja 5.32W max. adapter dolazi uz kameru. Nivo zaštite IP66, radna temperatura -30°C do +60°C. Materijal plastika.

Cijena i dobavljalivost na upit



imou



## IPC-S3EP-3M0WE

3MP Wi Fi bullet kamera full color

1/2.8" CMOS senzor. WI FI, IEEE802.11 b/g/n Dual antena. Mainstream 25/30fps (2304\*1296). IR do 30m. H.265. Fiksni objektiv 2.8mm, dvosmjerna komunikacija. Integriran mikrofoni i zvučnik. SD kartica max 256GB. Motion detection, detekcija ljudi. Uz kameru dolazi adapter 12V, 1A. IP67 Access by a cloud (P2P), podržava Android i iPhone: besplatna aplikacija IMOU.

VK-1112

Cijena i dobavljenost na upit

imou



## IPC-GS7EP-3M0WE kamera Rasprodaja

3 MP WI-FI pokretna PTZ kamera

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 2304x1296. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integriran mikrofoni, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart Full Color, noćna vidljivost do 30 m. Slot za Micro SD karticu do 256GB. Dualna antena 120m domet na otvorenom, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12VDC, 1A - adapter dolazi uz kameru. Nivo zaštite IP66 - Materijal plastika.

VK-1075

Cijena i dobavljenost na upit

imou



## KIT/IPC-K9EP-3T0TE-EU/FSP12-TYPEC

3 MP 4G pokretna PT kamera sa solarnim panelom

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 2304x1296. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integriran mikrofoni, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart, PIR senzor, noćna vidljivost do 20 m. 15000mAh baterija. Slot za Micro SD karticu do 256GB. 4G SIM modul, ImouLife aplikacija za iOS, Android. Napajanje 5VDC, 2A - podrška za IMOU solarni panel. Nivo zaštite IP66 - Materijal plastika.

VK-1131

Cijena i dobavljenost na upit

imou



## IPC-K9EP-3T0WE/FSP12-TYPEC

3 MP WI-FI pokretna PT kamera sa solarnim panelom

1/2.8" CMOS sa progresivnim skeniranjem. Rezolucija 2304x1296. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integriran mikrofoni, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart, PIR senzor, noćna vidljivost do 20 m. 15000mAh baterija. Slot za Micro SD karticu do 256GB. Dualna antena 50m domet na otvorenom, ImouLife aplikacija za iOS, Android. Napajanje 5VDC, 2A - podrška za IMOU solarni panel. Nivo zaštite IP66 - Materijal plastika.

VK-1165

Cijena i dobavljenost na upit

imou



## FSP12 Solarni panel za IPC-B46LP

Solarni panel za IPC-B46LP

VK-935-1

Cijena i dobavlјivost  
na upit

imou



## IPC-A42P-L pokretna kamera

4 MP Wi Fi pan tilt pokretna kamera

VK-891-1

1/2.7" progressive CMOS senzor,WI-FI IEEE 802.11 b/g/n, Main stream frame rate: 25 fps @ 1080p , IR LED dometa do 10m, H.265&H.264, fiksni objektiv 3.6mm. Mikrofon i zvučnik ugrađeni, Two-way talk, Micro SD Max 256GB, Motion Detection, Configurable Region, Human Detection, Abnormal Sound Alarm, Smart Tracking, Privacy Mode, DC5V Max 5W (adapter 5V 1A dolazi uz kameru). Podržava Android i IOS: besplatna aplikacija IMOU.

Cijena i dobavlјivost  
na upit

imou



## IPC-F42P bulit kamera

4MP Wi-Fi kamera u bullet kućištu

VK-1080

1/2.7"4 Megapixel Progressive CMOS. Noćni mod do 30 m. Fiskni objektiv 2.8mm/3.6mm/6mm. Video kompresija H.265/H.264. Maksimalno do 30frejmova. Integrisan mikrofon. Detecija pokreta i ljudi. SD kartica do 256 GB. Radna temperatura -30°C do +55°C. Napajanje 12V/0.5A.Zaštita IP67.Materijal plastika.

Cijena i dobavlјivost  
na upit

imou



## IPC-T42EP Wifi Dome kamera

4MP Wi-Fi kamera u turret kućištu

VK-991

1/2.8" CMOS senzor sa progresivnim skeniranjem.Wi-Fi:IEEE802.11b/g/n, Dual Antena. Domet IR-a 30 m Fiksni objektiv 2.8mm/3.6mm. Video kompresija H.265/H.264.Integrirani mikrofon. SD kartica max 256GB. Motion detekcija, detekcija ljudi. Napajanje 12V 0.5A. Potrošnja <3W. Plastično kućište. Access by a cloud (P2P), podržava Android i iPhone: besplatna aplikacija IMOU.

Cijena i dobavlјivost  
na upit

imou



## IPC-B46LP Imou kamera Rasprodaja

4MP baterijska bežična smart kamera

VK-935

1/2.9" Progressive CMOS senzor, bežična kamera sa punjivom baterijom. Izdržljivost baterije do 6 mjeseci, micro USB power port. Fiksni objektiv 2.8mm IR LED dometa 10m, domet LED za Full Color 5m. Ugao gledanja 110 ° ( H) 61 ° ( D). Video kompresija H.264/H.265. Dvosmjerna komunikacija, ugrađen mikrofon, zvučnik, sirena 110dB i spotlight. PIR detektor i detektor ljudi. WI-FI dual 2.4 GHz & 5 GHz. SD kartica do 128GB. Nivo zaštite IP65, radna temperatura -20°C do + 50°C.

Cijena i dobavlјivost  
na upit

imou



## IPC-F46FEP-D WiFi bullet kamera Rasprodaja

4MP Wi-Fi kamera u bullet kućištu

VK-990

1/3" CMOS senzor sa progresivnim skeniranjem. WI FI,IEEE802.11 b/g/n Dual antena,100m open field. Main stream 25 fps. IR LED do 30m.Kompresija H.265/H264.Fiksni objektiv 2.8mm, dvosmjerna komunikacija. Integriran mikrofon i zvučnik.SD kartica max 256GB. Motion detection,detekcija ljudi.Uz kameru dolazi adapter 12V,1A. Zaštita IP67. Access by a cloud (P2P), podržava Android i iPhone: besplatna aplikacija IMOU.

Cijena i dobavlјivost  
na upit

imou



## IPC-S42FP pokretna kamera Rasprodaja

VK-893

4 MP pokretna P&T kamera full color

1/2.8" CMOS senzor. Wi-Fi:IEEE802.11b/g/n, Dual Antena 120m Open Field.Domet IR-a 30 m.Fiksni objektiv 3.6mm .Video kompresija H.265/H.264.Integrirani mikrofoni i zvučnik, sirena 110dB. Dvosmjerni audio. SD kartica max 256GB.Motion detekcija, detekcija ljudi.Napajanje 12V 1A, (dolazi uz kameru). Potrošnja <6.2W. Plastično kućište. Zaštita IP66.Access by a cloud (P2P), podržava Android i iPhone: besplatna aplikacija IMOU.

Cijena i dobavljenost  
na upit

imou



## IPC-S6DP-5M0WEB-E27 kamera

5 MP WI-FI pokretna PT kamera u obliku sijalice

1/2.7" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 2.8mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofon, zvučnik, sirena. Kompresija H.265/H.264. Smart Full Color, noćna vidljivost do 25 m. Slot za Micro SD karticu do 256GB. ImouLife aplikacija za iOS, Android. Napajanje 00~240 V. Materijal plastika.

VK-1105

Cijena i dobavlјivost na upit

imou

## IPC-S3EP-5M0WE bulet kamera

5 MP Wi-Fi kamera u bullet kućištu

1/3" 5 Megapixel Progressive CMOS. Noćni mod do 30 m. Fiskni objektiv 2.8mm/3.6mm. Video kompresija H.265/H.264. Maksimalno do 30frejmova. Integrisan mikrofon, sirena, 110db. Detecija pokreta, vozila i ljudi. SD kartica do 256 GB. Radna temperatura -30°C do +50°C. Napajanje 12V/1A. Zaštita IP67. Materijal plastika i metal.

VK-1102

Cijena i dobavlјivost na upit

imou



## IPC-GS7EP-5M0WE kamera

5 MP WI-FI pokretna PT kamera

1/2.7" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofon, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart Full Color, noćna vidljivost do 30 m. Slot za Micro SD karticu do 256GB. Dualna antena 120m domet na otvorenom, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12V, 1A. Nivo zaštite IP66 - Materijal plastika.

VK-1076

Cijena i dobavlјivost na upit

imou



## IPC-K3DP-5H0WF

5 MP Wi-Fi kamera u bullet kućištu

1/3" 5 Megapixel Progressive CMOS. Noćni mod do 30 m. Fiskni objektiv 2.8mm/3.6mm. Video kompresija H.265/H.264. Maksimalno do 30frejmova. Integrisan mikrofon, Detecija pokreta, vozila i ljudi. SD kartica do 256 GB. Radna temperatura -30°C do +60°C. Napajanje 12V/0.5A. Zaštita IP67. Materijal plastika

VK-1127

Cijena i dobavlјivost na upit

imou



## IPC-K7CP-5H1WE

5 MP WI-FI pokretna PT kamera

1/3" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofon, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart Full Color, detekcija covjeka, pametno praćenje, noćna vidljivost do 30 m. Slot za Micro SD karticu do 512GB. Dualna antena 120m domet na otvorenom, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12V, 0.5A. Nivo zaštite IP66 - Materijal plastika.

VK-1128

Cijena i dobavlјivost na upit

imou



## IPC-S7CP-5M0WE

5 MP WI-FI pokretna PT kamera

1/3" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofon, zvučnik, sirena 110dB. Kompresija H.265/H.264. Smart Full Color, detekcija covjeka, vozila, pametno praćenje, noćna vidljivost do 30 m. Slot za Micro SD karticu do 512GB. Dualna antena 120m domet na otvorenom, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12V, 1A. Nivo zaštite IP66 - Materijal plastika.

VK-1155

Cijena i dobavlјivost na upit

imou

NOVO



## IPC-K7FP-5H0TE-EU

VK-1157

5 MP 4G pokretna PT kamera

1/3" CMOS sa progresivnim skeniranjem. Rezolucija 2880x1620. Fiksna optika 3.6mm. Detekcija pokreta, detekcija ljudi, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB svijetlo upozorenja (crveno-plavo). Kompresija H.265/H.264. Smart Full Color, noćna vidljivost do 30 m. Slot za Micro SD karticu do 512GB. Integrisan 4G SIM modul, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12V, 1A. Nivo zaštite IP66 - Materijal plastika.

Cijena i dobavlјivost na upit

imou

NOVO



## IPC-S7DP-5M0WEZ

VK-1158

5 MP Wi-Fi dualna zoom pokretna PT kamera

1/3" CMOS sa progresivnim skeniranjem. Rezolucija 2592x1944. Fiksna dupla optika 2.8mm&12mm. Detekcija pokreta, detekcija ljudi, detekcija vozila, dvosmjerna komunikacija, integrisan mikrofoni, zvučnik, sirena 110dB svijetlo upozorenja. Kompresija H.265/H.264. Smart Full Color, pametno praćenje, noćna vidljivost do 56 m. Slot za Micro SD karticu do 512GB. Wi-Fi antene, 1x100Mbps Ethernet Port, ImouLife aplikacija za iOS, Android. Napajanje 12V, 1A. Nivo zaštite IP66 - Materijal plastika.

Cijena i dobavlјivost na upit



imou



## IPC-S2XP-8M0WED

8 MP Wi-Fi dual lens pan tilt pokretna kamera

VK-1126

1/2.8"- 3" progressive CMOS senzor,WI-FI IEEE 802.11 b/g/n, Main stream frame rate:(fiksna)- 25 fps @ 2304x 1296-3MP,( pokretna)-25 fps @ 2880x1620-5MP , IR LED dometa do 15m, H.265&H.264, fiksni objektiv 3.6mm. Mikrofon i zvučnik ugrađeni, Two-way talk, Micro SD Max 256GB, Detekcija pokreta, Detekcija ljudi, Podesiva regija, Alarm za abnormalni zvuk, Detekcija kućnih ljubimaca., Smart Tracking, Privacy Mode, DC5V Max 5.75W (adapter 5V 1.5A dolazi uz kameru). Podržava Android i IOS: besplatna aplikacija IMOU.

Cijena i dobavlјivost  
na upit

imou



## IPC-S2XP-10M0WED

10 MP Wi-Fi dual lens pan tilt pokretna kamera

1/3" progressive CMOS senzor, Wi-Fi IEEE 802.11 b/g/n, Main stream frame rate:(dualna optika)- 25 fps @ 2880x1620 , IR LED dometa do 15m, H.265&H.264, fiksni objektiv 3.6mm. Mikrofon i zvučnik ugrađeni, Two-way talk, Micro SD Max 256GB, Detekcija pokreta, Detekcija ljudi, Podesiva regija, Alarm za abnormalni zvuk, Detekcija kućnih ljubimaca., Smart Tracking, Privacy Mode, DC5V Max 5.75W (adapter 5V 1.5A dolazi uz kameru). Podržava Android i IOS: besplatna aplikacija IMOU.

VK-1125

Cijena i dobavlјivost na upit



**imou**



## KIT/NVRT104HS-W-S2-CE-IT Set sa 4 kamere F22P

VK-961

WI FI SET KIT – 4xF22P IP WiFi kamere / 4-kanalni WiFi NVR, ugrađen 1TB HDD.

IP WiFi 2MP Bullet kamera, IC LED, 1/2.8" CMOS, progresivno skeniranje, Efektivni broj piksela 1920x1080, Fiksni objektiv 2.8mm (vidni ugao 102° horizontalno), 16x Digitalni zum, H.265/H.264 video kompresija, do 25/30 fps u svim rezolucijama, IC LE dioda dometa 30m, Detekcija pokreta, detekcija ljudi, Inkorporiran mikroskop, Reset taster, Micro SD slot (do 256GB), RJ-45 (1x100 Mbps) mrežni port, WiFi (Dual antena) IEEE802.11b/g/n, 2.4 GHz, Interoperabilnost – ONVIF, Podržava skladištenje na NVR, Cloud ili lokalno (uz Micro SD karticu),

Cijena i dobavlјivost na upit

**SONY**



## SNC-DH160 Network Camera AKCIJA

VS-174

1.4MP mrežna antivandal dome kamera sa 2.9x optičkim zumom

Cijena i dobavlјivost  
na upit



**WS-AHC324WZ-ICR-S4-AF bulit kamera**  
**Rasprodaja**

2MP AHD kamera u bullet kućištu sa StarLight tehnologijom, 4 u 1 TVI/AHD/CVI/CVBS režim.

0.001Lux/F1.2, 0Lux IR On. Maksimalna rezolucija 1920x1080. Motorizovana optika 2.8 - 12 mm. Nivo zaštite IP66. DWDR. Domet IC dioda 40 metara. 12v napajanje.

VK-637

Cijena i dobavlјivost  
na upit



## WS-D6116GT CCTV digitalni video recorder EB 16CH snimač

VR-413

**Rasprodaja** 16CH snimač

16 kanala TVI/AHD/CVI/IP/960H, snimanje 16x1080p@12fps/16x720p@25fps, podrška za Dropbox i Google Drive, P2P server za udaljeni nadzor, IP kamere 8Mbps/ch, HDMI, VGA, BNC, bekap putem USB-a, HDD-a ili preko mreže, 4 audio ulaza / 1 izlaz, RS485 za PTZ kontrolu, aplikacija za iPhone i Android, 2x SATA port za HDD do 8TB, 2x USB, napajanje 12V DC 3A

Cijena i dobavlјivost  
na upit

**dahua**  
TECHNOLOGY



## NKB1000-E mrežni snimač

Mrežna upravljačka tastatura sa LCD displejom

VO-213-1

Upravljanje Dahua digitalnim i mrežnim video snimačima, speed dome kamerama sa Dahua, Pelco-P i Pelco-D protokolom, Dahua IP Speed dome kamerama, Dahua IP dekoderima i Dahua Smart PSS softverom. Posедуje twist-to-zoom džojstik, RJ-45, RS232, RS485, RS422 i USB konekcija za povezivanje uređaja, mogućnost vezivanja sekundarnih tastatura, u kompletu sa napajanjem 220VAC/12VDC

Cijena i dobavlјivost  
na upit

**WISENET**



### SMT-1914/EX 19" LCD monitor Rasprodaja

SMT-1914/EX

SMT-1914 Maksimalna rezolucija : 1,280 x 1,024 Svjetlina : 250cd / m<sup>2</sup>. Kontrast : 1.000: 1, Vrijeme odziva : 5ms, Video sustav : NTSC / PAL, 1RGB-DVI priključak, Radna temperatura : 0 ~ 40 ° C, Dimenzije s postoljem ŠxVxD :412 x 347 x 59,4 mm

VM-030

Cijena i dobavljaljivost na upit

**WISENET**



### SMT-1934/EX 19" LCD monitor Rasprodaja

SMT-1934/EX LCD

SMT-1934 Maksimalna rezolucija : 1,280 x 1,024 Svjetlina : 250cd / m<sup>2</sup>. Kontrast : 1.000: 1, Vrijeme odziva : 5ms, Video sustav : NTSC / PAL, Video konektor : BNC (2 ulaza / 2 izlaza), RGB-DVI priključak , 1 HDMI ulaz, Audio priključak, 2 stereo ulaza, Zvučnici 2x1W, Radna temperatura : 0 ~ 40 ° C, Dimenzije s postoljem ŠxVxD :412 x 406.5mm x 217.4mm

VM-026

Cijena i dobavljaljivost na upit

**alhua**  
TECHNOLOGY



### LM24-F200 monitor

Monitor 23.8"

Monitor 23.8 , rezolucija FHD 1920x1080, kontrast 1000:1, pozadinsko osvjetljenje LED, 250 cd/㎡, ugao gledanja 178°(H)/178°(V), ulazi 1xVGA, 1xHDMI, dimenzije 602x490x116mm, radna temperatura 0°C~+40°C, potrošnja 23W, uz monitor dolazi HDMI i napojni kabal

VM-057

Cijena i dobavljaljivost na upit

**alhua**  
TECHNOLOGY



NOVO

### LM22-A200

Monitor 22"

Monitor 22"

VM-060

Cijena i dobavljaljivost na upit

**security**  
**MS**  
western



NOVO

### WS-ZK2400

WS-ZK2400 Monitor 24 Inch-a

Veličina panela: 23.8" LCD, Rezolucija piksela: 1920x1080 (FHD), Odnos stranica: 16:9, Svjetlost: 280cd/m<sup>2</sup>, Brzina osvježavanja: 75Hz, Kontrastni odnos: 3000:1, Vidni ugao: 178°, Vrijeme odziva: 6.5ms, Boja: 16.7M (8-bit), VGA ulazni signal: 1x VGA, HDMI ulazni signal: 1x HDMI, VESA montažna rupa: 75x75mm, Externi adapter: Niska potrošnja, životni vijek iznad 60.000 sati, Napajanje / Potrošnja energije: DC12V / ≤1W do ≤20W, Dimenzije bez stalka: 539.7mm (D) x 7mm (Š) x 320.95mm (V), Metod instalacije: Desktop postolje, montaža na zid, Jezik menija: Podržava više od 20 jezika (engleski, španski, francuski, ruski...), Materijal kućišta: Metal + ABS, Boja kućišta: Crna

VM-075-1

Cijena i dobavljaljivost na upit

**security**  
**MS**  
western



NOVO

### WS-ZK3200-S

WS-ZK3200-S Monitor 32 Inch-a

Veličina panela: 32 inča TFT LED, Rezolucija: Kompatibilan sa 4K@30Hz, Mod prikaza: 16:9, Svjetlost: 260cd/m<sup>2</sup>, Odnos kontrasta: 3000:1, Vidni ugao: 178/178°, Vrijeme odgovora: 6ms, Boje: 16.7M (8-bit), Video ulaz: RCA x3, VGA ulaz: VGA x1, HDMI ulaz: HDMI x2, USB port: USB x2, Audio: Ugrađeni zvučnik, Napajanje / Potrošnja energije: 100V/240V AC / ≤3W do ≤45W, Dimenzije: 731.05mm (Š) x 470.99mm (V) x 76mm (D), Težina: oko 5.6KG, Metod instalacije: Desktop postolje, montaža na zid, viseći nosač, Rupa za montažu na zid: 200x100mm, Jezici menija: Podržava kineski, engleski, španski, francuski... više od 20 jezika, Boja kućišta: Crna, Materijal kućišta: ABS; sa daljinskim upravljačem, Podrška za HDMI audio, sa stereo zvučnicima; ugrađeni sistem za praćenje temperature sa upozorenjem

VM-076-1

Cijena i dobavljaljivost na upit



NOVO



## WM-A1 NOSAČ MONITORA

VM-077

Cijena i dobavlјivost  
na upit



### EVT-PB1 + video baluni pasivni

VA-030

Video balun (transformator impedanse) za parični kabl – domet 600m  
par: predajnik + prijemnik

Cijena i dobavljenost na upit



### 3m AVIATION KABL

VO-404

Aviation kabl 6 m

kabl sa aviation konektorima za mobilne snimače, dužina 3 metra

Cijena i dobavljenost na upit



### AM-001P audio modul

VO-370

AM-001P audio modul

Cijena i dobavljenost na upit



### AM-001 audio modul

VO-160

Audio modul - mikrofoni - sa konektorima

Cijena i dobavljenost na upit



### PFM800-4K video balun

VA-029-2

Video balun sa kablom

Transmisija u realnom vremenu preko UTP CAT5E/6 kabl, kompatibilan sa HDCVI/TVI/AHD/CVBS

Cijena i dobavljenost na upit



### MCNU-GXF4-GXM4-6 AVIATION KABL 6m

VO-405

Aviation kabl 6 m

kabl sa aviation konektorima za mobilne snimače, dužina 6 metra

Cijena i dobavljenost na upit







## AM-02 mikrozvucni modul

Audio modul - mikrofoni

Širokopolasni audio modul, nadzor do 100m<sup>2</sup>, potrošnja 10mA, dimenzije 39.5x31x16 mm

VO-134

Cijena i dobavljenost na upit



## PFM790 naponska zaštita

PFM790 naponska zaštita

VO-369

Cijena i dobavljenost na upit



## PFM791 HDCVI izolator

Surge Protection

Zaštita od udara groma putem koaksijalnog kabela, BNC konektori (muško-ženski)

VO-374

Cijena i dobavljenost na upit



## 12m AVIATION KABL

Aviation kabl 12m

kabl sa aviation konektorima za mobilne snimače, dužina 12 metra

vo-409

Cijena i dobavljenost na upit



## PFM801 HDCVI baluna sa nap.

PFM801 HDCVI

Pasivni HDCVI video balun sa napajanjem DC 12V max 8W (100m) , DC12V 3W (200-300m), Udaljenost prenosa: 400m max za 720p i 200m max za 1080p. Kategorija kabela: UTP CAT 5E/6 (RPI10Ω/100M). Coax konektor: BNC-M. Podržane rezolucije za prenos: 720p/1080p. Anti-interferencija >60db. Temperaturno okruženje: -10 do +55 stepeni celzijusa, vlažnost od 0 do 95%

VA-031

Cijena i dobavljenost na upit



## LR1002 Long Reach Ethernet

Ethernet over coax pasivni konverter

Podržava IEEE802.3, IEEE802.3u standard, port: 1\*RJ45 10/100Mbps, 1\*BNC podržava RG59 koaksijalni kabal: 400m/100Mbps, 1000m/10Mbps, Podržava prenos napajanja na daljinu preko koaksijalnog kabela. Dolazi u paru.

VO-419-2

Cijena i dobavljenost na upit



SLIKA  
TRENUTNO NIJE  
DOSTUPNA

## BNC-5V Prenaponska zastita

BNC-5V Prenaponska zastita

VA-026

Cijena i dobavljaljivost  
na upit



## PFM140 mikrofon pin hole

PFM140 mikrofon pin hole

VO-372

Cijena i dobavljaljivost  
na upit



## Konverter AV HDMI na 3xRCA

Adapter konverter HDMI na 3xRCA Ž/Ž

VO-261

Cijena i dobavljaljivost  
na upit



## PFM811-C POC transmitter

PFM811-C POC transmitter

VO-222

Cijena i dobavljaljivost  
na upit



## ARB1606 relay extender

ARB1606 relay extender

VO-218

Cijena i dobavljaljivost  
na upit



## SAL-60 IR reflektor Rasprodaja

SAL-60 IR reflektor

VO-197

Cijena i dobavljaljivost  
na upit





## LR1002-1ET extender long range transmitter

VO-419-1

Ethernet over coax

Ethernet over Coax adapter; 1x 10/100 Mbps Base-TX; 1x BNC; Dometi za RG59B/U kabl: 400m/100Mbps, 1000m/10Mbps; Potrošnja <2W; U skladu sa IEEE802.3af i IEEE802.3at; U skladu sa IEEE802.3, IEEE802.3u, IEEE802.3x; Radna temperatura -30°C-65°C; Dimenzije 79mm×52mm×23mm; Masa 61g; Predajnik

Cijena i dobavlјivost na upit



## LR1002-1EC extender long range receiver

VO-419

Ethernet over coax

Ethernet over Coax adapter; 1x 10/100 Mbps Base-TX; 1x BNC; Dometi za RG59B/U kabl: 400m/100Mbps, 1000m/10Mbps; Potrošnja <2W; U skladu sa IEEE802.3af i IEEE802.3at; U skladu sa IEEE802.3, IEEE802.3u, IEEE802.3x; Radna temperatura -30°C-65°C; Dimenzije 79mm×52mm×23mm; Masa 61g; Prijemnik

Cijena i dobavlјivost na upit



## SAL-120 IR reflektor Rasprodaja

VO-199

SAL-120 IR reflektor

Cijena i dobavlјivost na upit



## SAL6-70B IR reflektor Rasprodaja

VO-198

SAL6-70B IR reflektor

Cijena i dobavlјivost na upit



## PFB510W nosač radara

VO-257-1

PFB510W nosač radara

Cijena i dobavlјivost na upit



## WS-A130 IR reflektor 130IR

VO-142

WS-A130 reflektor 130IR

Reflektor

Cijena i dobavlјivost na upit





## PFM141 mikrofon

PFM141 mikrofon

VO-373

Cijena i dobavlјivost  
na upit



## PFT2100 konvertor HDMI-HDCVI

PFT2100 konvertor HDMI-HDCVI

VO-363

Cijena i dobavlјivost  
na upit



## UPS SP 2000VA-1200W (IECx2+GERx2) Rasprodaja

UPS SP 2000VA-1200W (IECx2+GERx2)

VO-413-1

Cijena i dobavlјivost  
na upit



NOVO

## DH-PFM350-360

PFM350-360 UPS 600VA/360W

Širok raspon ulaznog napona: AC81~145V ili AC140~290V, ispunjava zahtjeve u različitim dijelovima za fluktuaciju električne mreže.

Pojačavanje i smanjivanje AVR za stabilizaciju napona. Punjenje u isključenom stanju, funkcija hladnog pokretanja i potpuna zaštita.

Kontinuirano napajanje za sprječavanje gubitka podataka.

Kompaktna veličina.

VO-460

Cijena i dobavlјivost  
na upit

NOVO Nov proizvod

Proizvod u dolasku

Pozovite za više informacija o raspoloživosti

**WD** Western Digital



## HDD WD NOT 10JPVX Rasprodaja

HD-030

HDD WD NOT 10JPVX

Cijena i dobavlјivost  
na upit

**SEAGATE**



## HDD SEGATE 4TB 128 MB ST4000LM024-bez kablа

HD-040-1

HDD SEGATE 4TB 128 MB ST4000LM024

Cijena i dobavlјivost  
na upit

**SEAGATE**



## ST8000VX010 HDD 8TB

HD-041-3

ST8000VX010 HDD 8TB

ST8000VX010 HDD 8TB

Cijena i dobavlјivost  
na upit

**SEAGATE**



## ST10000VE001 HDD 10TB

HD-042-2

Hard disk 10TB, SATA 6Gb/s

3,5", 256MB, SkyHawk serija predviđena za korišćenje u sistemima za video nadzor

Cijena i dobavlјivost  
na upit

**SEAGATE**



## ST10000NM017B HDD

HD-046

ST10000NM017B HDD 10TB

Cijena i dobavlјivost  
na upit

**SEAGATE**



## ST12000VE001 12TB

HD-047

ST12000VE001 HDD 12TB

ST12000VE001 HDD 12TB

Cijena i dobavlјivost  
na upit





## ST16000VE002

Hard disk 16TB, SATA 6Gb/s

3,5", 256MB, SkyHawk serija predviđena za korišćenje u sistemima za video nadzor

HD-048

Cijena i dobavljaljivost na upit



## ST1000VX013 HDD

ST1000VX013

ST1000VX013

HD-049

Cijena i dobavljaljivost na upit



## ST4000VX016 HDD 4TB

Hard disk 4TB, SATA 6Gb/s

3,5, 256MB, serija predviđena za korišćenje u sistemima za video nadzor

HD-037-4

Cijena i dobavljaljivost na upit



## HDWT720UZSVA 2TB

Hard disk 2TB, SATA 6Gb/s

3,5, 5400rpm, 128MB, S300 serija predviđena za korišćenje u sistemima za video nadzor

HD-034-9

NOVO

Cijena i dobavljaljivost na upit



## HDWT860UZSVA 6TB

Hard disk 6TB, SATA 6Gb/s

3,5, 5400rpm, 256MB, S300 serija predviđena za korišćenje u sistemima za video nadzor

HD-035-3

NOVO

Cijena i dobavljaljivost na upit



## HDWT840UZSVA 4TB

Hard disk 4TB, SATA 6Gb/s

3,5, 5400rpm, 256MB, S300 serija predviđena za korišćenje u sistemima za video nadzor

HD-037-5

NOVO

Cijena i dobavljaljivost na upit





NOVO

## HDWT31AUZSVA 10TB

Hard disk 10TB, SATA 6Gb/s

3,5, 7200rpm, 256MB, S300 serija predviđena za korišćenje u sistemima za video nadzor

HD-042-3

Cijena i dobavljaljivost na upit



NOVO

## HDWV110UZSVA

Hard disk 1TB, SATA 6Gb/s

3,5, 5700rpm, 64MB, S300 serija predviđena za korišćenje u sistemima za video nadzor

HD-049-1

Cijena i dobavljaljivost na upit

**TF-C100/64GB**

SD-013

MicroSD kartica kapaciteta 64GB.

Čitanje 95mb/s, upis 30mb/s. File system FAT32. Radna temperatura od 0 do 70 stepeni.

Cijena i dobavljivost  
na upit

Imou

**ST2-64-S1 SD kartica 64 GB**

SD-012

ST2-64-S1 SD kartica 64GB

Cijena i dobavljivost  
na upit**SDC4/4GB kartica**

SD-002

SDC4/4GB kartica

Cijena i dobavljivost  
na upit

Imou

**ST2-128-S1 SD kartica 128GB**

SD-010

ST2-128-S1 SD kartica 128GB

Cijena i dobavljivost  
na upit**TF-P100/64GB kartica**

SD-001-1

MicroSD kartica kapaciteta 64GB.

Čitanje 100mb/s, upis 60mb/s. File system FAT32. Radna temperatura od 0 do 70 stepeni.

Cijena i dobavljivost  
na upit**TF-P100/128GB kartica**

SD-007-1

MicroSD kartica kapaciteta 128GB.

Čitanje 100mb/s, upis 90mb/s. File system FAT32. Radna temperatura od 0 do 70 stepeni.

Cijena i dobavljivost  
na upit



Imou



## ST2-256-S1 SD kartica 256GB

ST2-256-S1 SD kartica 256GB

SD-011

Cijena i dobavljenost  
na upit

DAHUA  
TECHNOLOGY



## TF-P100/256GB kartica

TF-P100/256GB kartica

SD-009

Cijena i dobavljenost  
na upit



## PFA12A baza

Nosač za kamere

Nosač za Dahua kamere 210.9mmx97.5mmx35mm, strukturni vodootporan dizajn, mogućnost skrivanja kablova unutar nosača, može se postaviti video balun za HDCVI/AHD/TVI/CVBS kamere

VO-418

Cijena i dobavlјivost na upit



## PFA100 nosač Rasprodaja

Nosač za kamere

PFA100 nosač

VO-375

Cijena i dobavlјivost na upit



## PFA114 nastavak za PTZ

Nosač za PTZ kameru

Mount adapter za PTZ kameru · Dimenzije: 60mm x 50.5mm · Radni temp. opseg: -40°C ~60°C · Opteretivost: do 7 kg ·

VO-396

Cijena i dobavlјivost na upit



## PFA110 nosač

Nastavak za PFB300C

Nastavak za PFB300C za PTZ kamere 59x53mm

VO-385

Cijena i dobavlјivost na upit



## PFA135 nosač kamere

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera.

Dimenzije 90mm(prečnik) x 35mm. Vodootporna.

Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF file sa specifikacijama

VO-360

Cijena i dobavlјivost na upit



## PFA13B baza za kameru

PFA13B baza za kameru

VO-386

Cijena i dobavlјivost na upit



## PFA101 nosač kamere

VO-442

Nosač kamera

Plafonski nosač za kamere, aluminijum , dimenzije 159x35mm ,težina 0.24kg, maksimalno opterećenje 3 kg, bjela boja

Cijena i dobavlјivost  
na upit




## PFA102 nosač za kamere

VO-388

PFA102 nosač za kamere

Cijena i dobavlјivost  
na upit



## PFA134 baza kamere 90x33.7mm

VO-367

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera.

Dimenzije 90mm(prečnik) x 35mm. Vodootporna. Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF file sa specifikacijama

Cijena i dobavlјivost  
na upit



## PFA139 nosač

VO-393

Vodootporna nazidna dozna za instalaciju kamera.

Vodootporna aluminijumska dozna, Dimenzije 108.0x28.5mm. Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF file sa specifikacijama.

Cijena i dobavlјivost  
na upit



## PFA105 nosač fisheye

VO-395

Nosač za fisheye kamere

Mount adapter za Fisheye kamere · Dimenzije: 154.9mmx80.5mm · Materijal: aluminijum · Radni temp. opseg: -40°C ~60°C / <90% RH · Opteretivost: do 1 kg

Cijena i dobavlјivost  
na upit



## PFA13G nosač za kameru

VO-429

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera

Aluminijumska dozna, Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

Cijena i dobavlјivost  
na upit





## PFA13A-E nosač kamere

VO-400-1

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera

Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

Cijena i dobavlјivost na upit



## PFA137 nosač kamere

VO-354

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera.

Od aluminijuma, dimenzije 122.0mm x34.2mm, nosivost 1kg

Cijena i dobavlјivost na upit



## PFA136 nosač kamere

VO-361

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera.

Od aluminijuma, dimenzije 115.5mm x34mm, nosivost 1kg

Cijena i dobavlјivost na upit



## PFB203W nosač kamere

VO-350

Nosač za zidnu montažu

Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

Cijena i dobavlјivost na upit



## PFB300S nosač

VO-384

Zidni nosač za kamere

Water proof zidni nosač sa nazidnom kutijom za montažu, 228X115X160 IP66, -40 do 60C

Cijena i dobavlјivost na upit



## PFB204W nosač/baza kamera 160x122x76mm


VO-401

Aluminijumski nosač za zidnu montažu

Dimenzije 160 x 122 x 76mm, nosivost 1kg, težina 0.5kg. Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

Cijena i dobavlјivost na upit






## PFA152-E nosač kamere

Aluminijumski nosač, odgovara banderama prečnika Ø80~150mm

Pogledati tabelu podržanih kamera

VO-348-1

Cijena i dobavlјivost na upit



## PFA130-E baza

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera

Aluminijumska dozna, IP66 zaštita. Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

VO-339-1

Cijena i dobavlјivost na upit



## PFA154 nosač za stub Rasprodaja

PFA154 nosac za stub

VO-423

Cijena i dobavlјivost na upit



## PFA120 Nosac PTZ 115X160X35 mm

PFA120 vodotporna razvodna kutija

PFA120 vodotporna razvodna kutija, dimenzija 115 x 160 mm, za ugaoni nosač PFB305W.

VO-340

Cijena i dobavlјivost na upit



## DH-PFB200C ugradni nosač

Ugradni nosač

pFB200C ugradni nosač

VO-387

Cijena i dobavlјivost na upit



## PFA123-V2 nosač

PFA123-V2 nosač

VO-265

Cijena i dobavlјivost na upit



## PFA138 baza

VO-417

Nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera.

Od aluminijuma, dimenzije 116.0mm x38mm, nosivost 3kg

Cijena i dobavlјivost na upit



## PFB300C nosač za plafonsku montažu

VO-353

Nosac Dahua kamere

Nosac Dahua kamere za plafonsku montazu

Cijena i dobavlјivost na upit



## PFA121-V2 baza kamere

VO-355

Vodootporna nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera

IP66, materijal:aluminijum, dimenzije: (ŠxDxV) 134mm x 134mm x 55mm, temperatura: -40°C ~60°C, nosivost 3kg, težina 0.55kg, Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF fajl sa specifikacijama

Cijena i dobavlјivost na upit



## PFA122-V2 baza IP66 134X134 mm

VO-346

Vodootporna nazidna dozna za sakrivanje kablova i konektora prilikom instalacije kamera

IP66, materijal:aluminijum, dimenzije: (ŠxDxV) 134mm x 135mm x 56mm, temperatura: -40°C ~60°C

Cijena i dobavlјivost na upit




## PFB302S nosač

VO-376

Zidni nosač

Water proof zidni nosač sa nazidnom kutijom za montažu, 134X134X187.5 IP66, -40 do 60C

Cijena i dobavlјivost na upit



## PFA151 nosac kamere za ugaonu montažu

VO-351

Nosač Dahua kamere

Nosač Dahua kamere za ugaonu montažu 243x170 138mm

Cijena i dobavlјivost na upit





## PFA150-V2 nosač

VO-368-1

Nosač za banderu

Aluminijumski nosač, odgovara banderama prečnika Ø80~150mm

Cijena i dobavlјivost  
na upit




## PFA137 BLACK

VO-354-1

Vodootporna nazidna dozna za instalaciju kamera.

Vodootporna aluminijumska dozna, Dimenzije Ø122.0mm.0x34.2mm. Za detaljne informacije o kompatibilnim modelima, molim Vas pogledajte PDF file sa specifikacijama.

Cijena i dobavlјivost  
na upit



## PFB2211C

VO-459

PFB2211C Plafonski nosač

PFB2211C Plafonski nosač 125.9 mm × 475.0 mm–125.9 mm × 800.0 mm

Cijena i dobavlјivost  
na upit



## Adapter 12V 500mA

12V/500mA

Adapter stabilisani 12Vdc/500mA čoperski

VN-032

Cijena i dobavlјivost  
na upit



## Adapter 12V 1A PFM321D-EN

PFM321D-EN

Adapter stabilisani 12Vdc/1A Dahua

VN-033-1

Cijena i dobavlјivost  
na upit



## Adapter 12V 1A CP1000-D

Adapter desktop DC12V / 1A

Input voltage: AC 100-240V, 50-60Hz, Output voltage: DC12V, 1 amper, radna temperatura -20-60°C, težina 207g, dimenzije 98.5x46.8x32mm

VN-033

Cijena i dobavlјivost  
na upit



## PFM320-010EN adapter 12VDC 1A

PFM320-010EN adapter 12VDC 1A

PFM320-010EN adapter 12VDC 1A, V nivo energetske učinkovitosti

VN-081

Cijena i dobavlјivost  
na upit



## PFM320-020EN adapter 12VDC 2A

PFM320-020EN adapter 12VDC 2A

PFM320-020EN adapter 12VDC 2A V nivo energetske učinkovitosti

VN-082

Cijena i dobavlјivost  
na upit



## PFM320D-EN Adapter 12V/2A

12V 2A Napajanje

12V 2A Napajanje u plastičnom kućištu sa EU konektorom za 220v i DC konektorom za 12v dimenzija sa ušicama za kačenje 104x45x33mm

VN-071

Cijena i dobavlјivost  
na upit





## Adapter HT3000 12V 3A

AC100-240V, DC12V, 3A, sa napojnim kablom

VN-061

Cijena i dobavljenost  
na upit



## PFM300 adapter 12VDC 2A

PFM300 adapter 12VDC 2A

PFM300 adapter 12VDC 2A za zidnu montažu sa strukturalnom vodootpornošću i V-0 zaštitom od požara

VN-080

Cijena i dobavljenost  
na upit



## PFM320D-015 adapter 12V 1.5A

Napajanje za doznu DC12V 1.5A

Jednostavna instalacija,

VN-072

Cijena i dobavljenost  
na upit



## Adapter 12V 3A CP3000-VI

Adapter 12V/ 3A (CP3000-VI)

Adapter stabilisani 12Vdc/ 3A čoperski (Ugrađen filter za smetnje)□

VN-059

Cijena i dobavljenost  
na upit



## DH-PFM344D-4CH-EN adapter 12 4 izlaza 48W

Adapter 12V 4 izlata 48W

VN-077

Cijena i dobavljenost  
na upit



## Adapter 12V/5A CP5000-VI

AC100-240V, DC12V, 5A, sa napojnim kablom

Ispunjava sve sertifikate, nivo efikasnosti 6

VN-074

Cijena i dobavljenost  
na upit





## Adapter 12V 5A/4CH CP1205000-4

VN-060

5A - stabilisani ispravljač 220Vac/12Vdc - čoper

Reglete za priključivanje 4 kamere. Zaštita od kratkog spoja.

Cijena i dobavljenost na upit




## PFM344D-8CH-EN adapter 12V 8 izlaza 60W

VN-078

Adapter 12V 8 izlaza 60W

Cijena i dobavljenost na upit



## 12V 5A/9CH HT1209-5A centralna napajanja

VN-062

Napajanje u metalnom kućištu, DC12V / 5A 9CH

Input voltage: AC 100-240V, 50-60Hz, Output voltage: DC11.8V-14V, 5 ampera, 9 kanala, radna temperatura -20-60°C, težina 1,66kg, dimenzije 201.5x238.5x61.5mm

Cijena i dobavljenost na upit



## HTD-120W-B (A24300-230) napojna jedinica

VN-067

HTD-120W-B napojna jedinica sa backup funkcijom

Napojna jedinica AC 100-240Vac/ 12V/10A sa Back-up funkcijom

Cijena i dobavljenost na upit



## Transformator 100 VA 230/24V

VN-070

Transformator 100 VA 230/24V

Cijena i dobavljenost na upit



## 12V 5A/9CH HT1209-5A-W centralno napajanje sa WPRF kućište

VN-063

Napajanje u vodootpornom metalnom kućištu, DC12V 5A 9CH

Input voltage: AC 100-240V, 50-60Hz, Output voltage: DC12V, 5 ampera, 9 kanala, radna temperatura -20-60°C, težina 3,6kg, dimenzije 310x279x91mm

Cijena i dobavljenost na upit






### Centralno napajanje 12V/10A/9CH HTI209-10A

Centralno napajanje 12V/10A/9CH  
(HTI209-10A)

Centralno napajanje AC100-240V/ DC12V/  
10A/ 9ch, 9 izlaza sa elektronskom zaštitom  
svakog izlaza (2.2A autoreset) u metalnoj  
kutiji 250 x 215 x 59mm Sertifikat  
CE,FCC,ROHS

VN-064-1

Cijena i dobavlјivost  
na upit



### 12V 10A/18CH HTI218-10A centralno napajanje

Napajanje u metalnom kućištu, DC12V  
10A 18CH

Input voltage: AC 100-240V, 50-60Hz, Output  
voltage: DC11.8V-14V, 10 ampera, 18 kanala,  
radna temperatura -20-60°C, težina 1,66kg,  
dimenzije 201.5x238.5x61.5mm

VN-064

Cijena i dobavlјivost  
na upit



### 12V 5A/9CH CP1209-5A-B sa back -up funkcijom

CCTV UPS, DC12V/5A/9CH

Input voltage: AC 100-240V, 50-60Hz, Output  
voltage: DC13.5V +/-1V, 5 ampera, 9 kanala,  
radna temperatura -20-60°C, težina 2,14kg,  
dimenzije 264x206x90mm

VN-068

Cijena i dobavlјivost  
na upit



### 12V 10A/18CH HTI218-10A W centralno napajanje sa WPRF kućištem

Napajanje u vodootpornom metalnom  
kućištu, DC12V 10A 18CH

Input voltage: AC 100-240V, 50-60Hz, Output  
voltage: DC12V, 10 ampera, 18 kanala, radna  
temperatura -20-60°C, težina 3,6kg,  
dimenzije 310x279x91mm

VN-065

Cijena i dobavlјivost  
na upit




### TAM01GT01GT-75 - POE NAPAJANJE

TAM01GT01GT-75

Hi-PoE injektor 75W, portovi 1 x 10/100/1000  
Base-T, 1 x 10/100/1000 Base-T( PoE power  
supply), podržava PoE ekstender PFT1300  
(kaskadnim vezanjem 2 ekstendera mogu se  
povezati max 3 IP kamere na max  
udaljenosti 300m, radna temperatura -30°C~  
65°C,

MO-143

Cijena i dobavlјivost  
na upit




### 12V 10A/18CH CP1218-10A-B sa back-up funkcijom

CCTV UPS, DC12V/10A/18CH

Input voltage: AC 100-240V, 50-60Hz, Output  
voltage: DC13.5V +/-1V, 10 ampera, 18 kanala,  
radna temperatura -20-60°C, težina 2,24kg,  
dimenzije 264x206x90mm

VN-069

Cijena i dobavlјivost  
na upit



## 12V 20A/18CH CP1218-20A centralno napajanje

VN-066

Napajanje u metalnom kućištu, DC12V / 20A 18CH

Input voltage: AC 100-240V, 50-60Hz, Output voltage: DC11V-15V, 20 ampera, 18 kanala, radna temperatura -20-60°C, težina 2,96kg, dimenzije 275x266x86mm

Cijena i dobavljenost  
na upit



## PFT1300 konvertor extender

PFT1300 konvertor extender

VO-389

Cijena i dobavljivost  
na upit



## PFM700-E extender

HDMI ekstender preko jednog UTP kabla

VO-362

Ulazni napon: 5VDC, prenos video signala u realnom vremenu bez kašnjenja, jaka otpornost na smetnje, daljina prenosa do 60m, podržava HDMI 1.3, zaštita od prenapona, lak za korišćenje

Cijena i dobavljivost  
na upit



## Alat za krimpovanje

Alat za krimpovanje i kompresovanje BNC, F i RCA kompresionih konektora

KK-042

Cijena i dobavljaljivost na upit



## PFM907-Tester Dahua Rasprodaja

PFM907-Tester Dahua

VO-233

Cijena i dobavljaljivost na upit



## PFM906-E

Tester za IP, HDCVI/AHD/TVI/CVBS i SDI kamere

Ekran dijagonale 7", IPS HD retina capacitive touch screen(1920x1200px), podržava IP, HDCVI/AHD/TVI/CVBS, SDI kamere, 3x 10/100M RJ45, 2x video in(SDI, HDCVI/TVI/AHD/CVBS), 1x video out, 1x TDR, 1x OPM, 1x VLS, 1x RS485, 1x DC12V in (napajanje), 1x HDMIulau, 1x HDMI izlaz, 1x audio ulaz, 1x audio izlaz, 1x Micro SD, PoE, DC12V 2A i USB 5V 2A izlaz za napajanje, integrisana baterija velikog kapaciteta 37Wh, podržava TDR (network cable/coaxial cable), tester za UTP i optičke kablove, funkcija digital multi-meter, funkcija ispitivanja optičke snage.

VO-232-3

Cijena i dobavljaljivost na upit



## PFM906 Tester Dahua

Tester za IP, HDCVI/AHD/TVI/CVBS i SDI kamere

Ekran dijagonale 7", IPS HD retina capacitive touch screen(1920x1200px), podržava IP, HDCVI/AHD/TVI/CVBS, SDI kamere, 3x 10/100M RJ45, 2x video in(SDI, HDCVI/TVI/AHD/CVBS), 1x video out, 1x TDR, 1x OPM, 1x VLS, 1x RS485, 1x DC12V in (napajanje), 1x HDMIulau, 1x HDMI izlaz, 1x audio ulaz, 1x audio izlaz, 1x Micro SD, PoE, DC12V 2A i USB 5V 2A izlaz za napajanje, integrisana baterija velikog kapaciteta 37Wh, podržava TDR (network cable/coaxial cable), tester za UTP i optičke kablove, funkcija digital multi-meter, funkcija ispitivanja optičke snage.

VO-232-1

Cijena i dobavljaljivost na upit

Nov proizvod

Proizvod u dolasku

Pozovite za više informacija o raspoloživosti



## BNC/F-RCA/M konektor

BNC ženski - Činč muški

KK-034

Cijena i dobavljenost  
na upit



## DC/F konektor ženski za napajanje PFC

DC/PFC konektor

VO-358

Cijena i dobavljenost  
na upit



## Konektor F (RG59)

Konektor F (RG59)

KK-044

Cijena i dobavljenost  
na upit



## F/F-BNC/M konektor bez F

F/F-BNC/M konektor bez F

KK-048

Cijena i dobavljenost  
na upit



## F/F-RCA/M konektor

F ženski - Činč muški

KK-047

Cijena i dobavljenost  
na upit



## F/M-F/F

F muški - F ženski

KK-049

Cijena i dobavljenost  
na upit





## BNC-KRIMP konektor

KK-030

BNC, RG59, krimp, muški, proizvod se prodaje bez garancije, cena je na komad. Minimalna količina za kupovinu 10 komada.

Cijena i dobavlјivost  
na upit



## BNC-T konektor

KK-031

BNC muški - 2xBNC ženski

Cijena i dobavlјivost  
na upit



## BNC-Spring-2

KK-051

BNC muški, RG59, na šraf

Cijena i dobavlјivost  
na upit



## BNC/M-BNC/M konektori

KK-046

BNC/M-BNC/M konektori

Cijena i dobavlјivost  
na upit



## Konektor F kompresioni RG59

KK-055

Konektor F kompresioni RG59

Cijena i dobavlјivost  
na upit



## Split cabel 1-4

VN-035

Račva 4 na 1

Cijena i dobavlјivost  
na upit







## BNC/M-RCA/F konektor

BNC/M-RCA/F konektor

BNC/M-RCA/F konektor

KK-033

Cijena i dobavlјivost  
na upit




## F/F-BNC/M konektor

F/F-BNC/M konektor

F/F-BNC/M konektor

KK-032

Cijena i dobavlјivost  
na upit



## PFM976-BNCQ9P

Muški BNC konektor za RG59

KK-051-1

Cijena i dobavlјivost  
na upit



## DC/M konektor PFM979-DCP

PFM979-DCP

konektor muški za napajanje DC/M

VO-200-1

Cijena i dobavlјivost  
na upit



## PFM976-631-PT

RJ45 konektori (100kom) kutija

VO-445-1

Cijena i dobavlјivost  
na upit





## Kabal 6x0.22 (100m)

Alarmni kabal

6x0.22mm (pakovanje kotur 100m)

AK-011

Cijena i dobavlјivost  
na upit



## Alarmni kabal 2x0.5 + 4x0.22mm

Alarmni kabal

2x0.5mm + 4x0.22mm (pakovanje kotur 100m)

AK-030-1

Cijena i dobavlјivost  
na upit




## RG59 koaksijalni kabal (100m)

KK-025

Koaksijalni kabl 75Ohm

100m

Cijena i dobavlјivost  
na upit



## RG59 koaksijalni kabal (200m)

KK-026

Koaksijalni kabl 75Ohm

200m

Cijena i dobavlјivost  
na upit



## RG59 koaksijalni kabal (500m)

KK-037

Koaksijalni kabl 75Ohm

500m

Cijena i dobavlјivost  
na upit



## Kabal RG59+2x0.75mm koaksijalni sa napojnim kablom (100 m)

KK-038

Koaksijalni kabl RG59 sa napojnim kablom 2x0.75

100m

Cijena i dobavlјivost  
na upit



## Kabal BNC-DC 50 m Rasprodaja

AK-007

Koaksijalni + napojni kabl sa konektorima

50m

Cijena i dobavlјivost  
na upit



## RG59+2X0,75/koaksijalni sa napojnim kablom (300 m)

KK-045

Koaksijalni kabl RG59 sa napojnim kablom 2x0.75

Kotur 300, crna boja, EASY PULL

Cijena i dobavlјivost  
na upit





## PFM941I-RG59N/2I-300

Koaksijalni kabl RG59 sa napojnim kablom 2x0.75mm

kotur 300m

KK-056

Cijena i dobavlјivost na upit



## PFM930-59N-100

Koaksijalni kabl 75Ohm

pakovanje 100m

KK-025-1

Cijena i dobavlјivost na upit



## RG59+2X0.75+1.3mm 100m

Koaksijalni kabl RG59 sa napojnim kablom 2x0.75mm i sajlom 1.3mm

pakovanje 100m

KK-057

Cijena i dobavlјivost na upit



## RG59+2X0.75+1.3mm 300m

Koaksijalni kabl RG59 sa napojnim kablom 2x0.75mm i sajlom 1.3mm

pakovanje 300m

KK-058

Cijena i dobavlјivost na upit

**TS 2V314 objektiv PENTAX Rasprodaja**

VO-009

TS 2V314 objektiv PENTAX

Cijena i dobavlјivost  
na upit

SLIKA  
TRENUTNO NIJE  
DOSTUPNA

**WS-MP0358AI optika 3.5-8mmAI Rasprodaja**

VO-151

WS-MP0358AI optika 3.5-8mmAI

Cijena i dobavlјivost  
na upit

WISENET

**SLA-2810D objektiv 2.8-10mmAI Rasprodaja**

VO-107

SLA-2810D objektiv 2.8-10mmAI

Cijena i dobavlјivost  
na upitFUJINON  
FUJIFILM**YV2.8x2.8LA-SA2L 2.8-8mm AI UT**

VO-135

2.8mm-8mm, auto-iris, vari-fokal

Cijena i dobavlјivost  
na upit

SLIKA  
TRENUTNO NIJE  
DOSTUPNA

**WS-10120D.IR 1.3Mpix 10-120mm Rasprodaja**

VO-202

WS-10120D.IR 1.3Mpix 10-120mm

Cijena i dobavlјivost  
na upitFUJINON  
FUJIFILM**YV10X5HR4A-SA2L 5-50mm Mpix**

VO-158

YV10X5HR4A-SA2L 5-50mm Mpix

Cijena i dobavlјivost  
na upit

SONY



## SNCA-360LENS optika 360 stepen Rasprodaja

Sony objektiv od 360 stepeni za SNC-CH140/CH240/CH220/CH120

VS-171

Cijena i dobavlјivost  
na upit



**SLIKA  
TRENUTNO NIJE  
DOSTUPNA**

## GL-500 nosač Rasprodaja

GL-500 nosač

VO-018

Cijena i dobavljaljivost  
na upit



## GL-208 nosač Rasprodaja

Metalni nosač za GL-618H i GL-619HB

kanal za prolaz kablova, dostupni u bež i  
silver boji

VO-022

Cijena i dobavljaljivost  
na upit



## GL 215 unutrašnji nosac-bez Rasprodaja

Metalni nosač za plafonsku montažu -  
lula, za GL-601/605/606

VO-081

Cijena i dobavljaljivost  
na upit